

PATENT APPLICATION SERIAL NO. 08 443430

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

*MDH
6-28-95*

~~110 MM 06/02/95 08443430~~

~~1 101~~

~~750.00 CK 780.296430X1~~

~~140 MM 06/09/95 08443430~~

~~1 101~~

~~750.00 CK 780.296430X1~~

140 MM 06/09/95 08443430

1 201

750.00 CK 780.296430X1

PTO-1556
(5/87)

Electronic Mail System With RF
Communications To Mobile Processors

Abstract OF THE DISCLOSURE

5 A system (100) for transmitting information from
one of a plurality of originating processors A-N to at
least a plurality of destination processors (A-N) which
may be transported during operation in accordance with
the invention includes at least one gateway
switch (14), a gateway switch storing information
10 received from one of the at least one originating
processor prior to transmission of the information to
the at least one destination processor; a
RF information transmission network (302) for
transmitting stored information received from one of
15 the at least one gateway switch by RF transmission to
at least one destination processor; at least one
interface switch (304), an interface switch connecting
a gateway switch to the RF transmission network and
transmitting stored information received from one of
20 the at least one gateway switch to the RF information
transmission network; and wherein the information is
transmitted to a receiving interface switch by the
electronic mail system in response to an address of the
receiving interface switch which has been added to the
25 information originated by the originating processor by
either the originating processor or gateway switch and
the information is transmitted from the receiving
interface switch to the RF information transmission
network with an address of the destination processor to
30 receive the information which has been added by either
the originating processor, a gateway switch or the
receiving interface switch.



780.29643X00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventors: THOMAS J. CAMPANA, JR., MICHAEL P. PONSCHKE,
and GARY F. THELEN

Invention: ELECTRONIC MAIL SYSTEM WITH RF
COMMUNICATIONS TO MOBILE PROCESSORS

Antonelli, Terry, Stout & Kraus
Suite 600
1919 Pennsylvania Avenue, N. W.
Washington, D. C. 20006

SPECIFICATION

To all whom it may concern:

Be it known that We, Thomas J. Campana, Jr., Michael P. Ponschke, and Gary F. Thelen, citizens of the United States, residing respectively at 3836 West 86th Street, Chicago, Illinois 60652; 212 Tara Drive, Lockport, Illinois 60441; and 16 Fox Lane, Palos Park, Illinois 60464; have invented certain new and useful improvements in

ELECTRONIC MAIL SYSTEM WITH RF
COMMUNICATIONS TO MOBILE PROCESSORS

of which the following is a specification.

Description
Electronic Mail System With RF
Communications to Mobile Processors

Technical Field

5 The present invention relates to electronic mail systems for transmitting information between processors.

Background Art

10 The use of computers to send and receive electronic mail messages is becoming very popular globally. Numerous companies (both network and software related) offer electronic mail packages (E Mail) and services. Currently, electronic mail services provide a convenient alternative to the more
 15 formal facsimile transmissions of memos and documents. Electronic mail is typically used to send relatively short informal messages between computers within an organization, or to a party located at a distant location or company. Electronic mail services are
 20 basically a wire line-to-wire line, point-to-point type of communications. Electronic mail, similar to facsimile transmissions, provides a one-way message. A recipient typically does not have to interact with the message. Electronic mail, unlike facsimile, is a
 25 non-real-time message transmission architecture.

30 Fig. 1 illustrates a block diagram of a typical electronic mail system 10 in commercial use such as by AT&T Corporation. The electronic mail system 10 is comprised of a plurality of single processors or groups of processors #1-#N with N being any number with each group having individual processors A-N with N being any number. The groups of processors #1-#N may be distributed at locations which are linked by the public

4

switch telephone network 12. The individual processors may be portable personal computers with a modem which are linked to the public telephone switch network 12 through wired or RF communications as indicated by a dotted line. Groups of associated processors #1-#3 may have diverse configurations with the illustrated configurations only being representative of possible architectures of groups of associated processors. The groups of associated processors may be connected to a host or mainframe computer through various communication mechanisms such as direct telephone communications (#1), communications through a local area network (#2), or communications through a private automatic branch exchange (#3). It should be understood that the illustrated architecture of the single and associated groups of processors is only representative of the state of the art with numerous variations being utilized. Many of the groups of associated processors are contained within the database network of a single company or organization located at distributed geographical locations throughout a country or in different countries.

Communications between an originating processor A-N, which may be any of the processors within the groups of associated processors #1-#3 or processor #N and a destination processor A-N are completed through the public switch telephone network 12 to one or more gateway ^{switches} with mailboxes 14 which function to store the message for delivery to the destination processor at a later point in time. The gateway switches with mailboxes 14 have a storage location, associated with each subscriber which may be any of the computers A-N within the associated groups of computers #1-#3 and individual computers #N, which provides retrieval capability of the electronic message.

SECRET

a

5

when it is not delivered directly to the destination processor A-N such as when the destination processor does not go directly off hook in response to an attempt to deliver the message from storage in the electronic mail gateway mailbox storage location associated with the destination processor. In order to originate an electronic mail message, the originating processor A-N calls an associated gateway switch with mailboxes 14 via telephone through the usage of a modem connection. This connection is made through the public switch network 12. A gateway switch with mailboxes 14 answers and provides a data connection to the originating processor A-N. The gateway switch with mailboxes 14 typically contains the originating processor A-N file and verifies that the sending processor is able to originate an electronic mail message via some form of password protection. Upon verification of the entry password, the electronic gateway switch with mailboxes 14 down loads software and entry screens that are displayed on the originating processor to permit a message to be composed. Thereafter, the message is composed and transferred from the originating processors gateway switch with mailboxes 14 to the destination processors gateway switch with mailboxes where the message is stored and an attempt is made to deliver the message to the destination processor via telephone connection through the public switch telephone network 12.

Electronic mail systems have several common items that must be entered in order to originate and send (format) an electronic message. These items include the destination address, which consists of either the person or company's name, an abbreviated form of the person's company or name, or a series of digits or alphanumeric characters that must be entered to

6

indicate to the electronic mail system the destination address of the recipient processor. Another item is an identification of the originating processor which may be an indication of the sender or the originator's name, company name, an abbreviated form of the originator's name or company name, or a numeric or alphanumeric entry that comprises the sender's name or address. This information is collectively an identification of the originating processor. Another item is the subject of the message which is typically a short reference as to the subject matter of the text or message that follows. Finally, the message or message text must be entered which is the information that is inputted by the person or machine which is originating the message at the originating processor A-N. Upon completion of the message text, the user or machine operating the originating processor A-N enters a series of commands or keystrokes on the originating processor to transmit the message to the gateway switch with mailboxes 14 associated with the originating processor A-N.

The transmission of the message from the originating processor's gateway switch with mailboxes 14 to the destination processor's electronic mail gateway switch with mailboxes is via analog or digital communications through the public switch telephone network. The destination gateway switch with mailboxes 14 contains the destination address of the recipient destination processor.

Upon arrival of the information at the destination processor's gateway switch with mailboxes 14, one of two events takes place. The information is typically stored in the destination processor's electronic mailbox for later retrieval by the destination processor through interaction by the user of the

destination processor. This typically happens as a result of the fact that a person is not located at the destination processor at the time of delivery of the message to the gateway switch with mailboxes 14 or the destination processor is not turned on and connected to the public switch telephone network 12. A second methodology is that the destination processor's gateway switch with mailboxes automatically dials the gateway processor's telephone number to deliver the information. In the situation where the destination processor is within a company or organization, the information may be delivered to the host computer. The destination processor's host computer stores the information until the destination processor calls the host computer to retrieve the information. In both of the methodologies described above, information delivery requires periodically calling a host computer or a mailbox at the gateway switch with mailboxes 14 to determine if new messages are present. This incurs additional costs in telephone calls and/or labor. If the host computer or gateway switch is not checked frequently, the information becomes untimely in its delivery. If the destination processor frequently checks the host computer or gateway switch, then additional costs and telephone calls and/or labor are encountered.

As personal computers are used more frequently by business travellers, the problem of electronic mail delivery becomes considerably more difficult. A business traveller carrying a portable PC has great difficulty in finding ^{Jack} telephone jacks to connect the PC to fetch electronic mail from either a host computer or a gateway switch. Connections for a PC's modem are difficult to find in airports and with the advent of digital PABX's in businesses and the telephone

8

connectors are incompatible with a PC's analog modem. Hotels and motels oftentimes have internal PABX's that prevent calls from automatically being placed by the user's PC to electronic mail gateway switches to retrieve information. Most portable PC modems will only operate correctly when connected to a true outside telephone line that has telephone battery voltages and dial tone available to permit the number to be dialed direct. The inability to find an appropriate connection to connect the PC modem when travelling has contributed to the degradation of electronic mail reception when the recipient is travelling. When travelling internationally, this problem is further compounded by the fact that most electronic mail gateway mailboxes require a 1-800 toll free number ^{to be} ~~is~~ dialed in order to connect the mailbox. Almost all 1-800 telephone numbers are available for continental use only and cannot be accessed from a foreign country.

Industry trends make it increasingly difficult to receive electronic mail. When PC's were exclusively considered an office or desktop machine, it was less difficult to deliver electronic mail. Advances in the state of the art in microelectronics have permitted PC's to be downsized to very lightweight portable (notebook), and notebook size computers. These portable units have the computing and storage power of the former desktop units and have lent themselves to the trend that they now become very portable in their utilization. They are small enough that they can easily fit into an attache case and/or a suit pocket. The net result is that the portable unit no longer resides in the office or the desktop. The portable unit now may be taken home at night, as well as on travel with the user, such as for business travel.

Increased portability of PC's further aggravates the problem of automatic electronic mail delivery as a consequence of portability eliminating the wired communication paths which have been typically used in state of the art electronic mail systems. The electronic mail industry is currently experiencing a rapid growth rate.

Numerous communication companies are offering forms of electronic mail services. However, a problem arises that users of one electronic mail system currently cannot send electronic mail to a subscriber of another electronic mail system (e.g., AT&T E-mail to Sprint Mail, etc.). Numerous attempts are currently underway in the industry to solve this problem. Current attempts are the utilization of common protocols between electronic mail systems (e.g. X.400). However, the proposed system does not resolve the problems resultant from portability and travelling situations described above.

Fig. 2 illustrates a diagram of a prior art network 100 developed by Telefind Corporation of Coral Gables, Florida, which provides worldwide paging and data transmission capability and is a preferred form of the RF information transmission network used in practicing the present invention. This network is described in detail in ~~the Assignee's~~ United States Patents 4,866,431, 4,868,558, 4,868,562, 4,868,860, 4,870,410, 4,878,051, 4,881,073, 4,875,039 and 4,876,538 and United States patent application Serial Nos. 409,390, 464,675, 465,894, 464,680, 429,615, 429,541, 409,605, and 456,742 which are incorporated herein by reference in their entirety. The system is a distributed network of switches comprised of a plurality of local switches 112, a plurality of lata switches 114 and a plurality of hub switches 116 with

each switch being located in a different geographical location within an area being serviced by the system. The hub switches 116 may be located totally within a country to provide national service or in multiple countries to provide international service. Only a single portion of the network is labelled with reference numerals with it being understood that repeating portions exist such as for that portion under the jurisdiction hub switch #P. Communication links which are illustrated as a dotted arrow represent network structure which has been omitted for clarity that is identical to structure that is illustrated in detail. Additionally, one or more sublocal switches may optionally be provided within the system under the jurisdiction of the local switch as described in the aforementioned patents. The sublocal switches have been omitted for purposes of clarity. Each switch has jurisdiction over a geographic area. The functions performed by the local switch 112, the data switch 114 and the hub switch 116 are described below. A local paging service 118 is typically connected to each of the local switches 112 which offers other paging services than that provided by the present invention although it should be understood that the local switch may be used exclusively to control all services offered at the local level. The local paging service 118 is typically an existing common carrier paging service which services an area within broadcast distance of a transmitter 115 under the jurisdiction of the local paging service to which the local switch 112 has been connected to permit the local paging service to function in the network to transmit pages to a plurality of paging receivers 119 (only one having been illustrated) connected to a peripheral device 119 which may be a data processor printer, telex service,

facsimile service or other types of data processing devices. The paging receivers automatically download data stored in their memory upon connection to a printer for producing a printout of the data. The
5 printer is sold with the receiver by Telefind Corporation of Coral Gables, Florida. The paging receivers 119 are described in United States Patents 4,849,750, 4,851,830, 4,853,688, 4,857,915, 4,928,100, 4,935,732, 4,978,944 and 5,012,235 and United States
10 Patent application Serial Nos. 381,483, 381,527, 597,350 and 662,616 which are assigned to Telefind Corporation of Coral Gables, Florida. The transmitter 115 may be either an analog or digital transmitter. Communications between the local, lata and hub switches
15 may be by any existing communication medium 120 such as direct dial-up circuits (IDD Circuits International), direct outward dial circuits (end-to-end), in-bound watts (and other in-bound services that are volume discounted), out-bound watts (and other out-bound
20 services that are volume discounted), feature group A (U.S. service), feature group B (U.S. and European services), MF tie trunks (U.S. and European services), and direct inward dial (international service, where available), as well as any future medium which permits
25 pages to be transmitted between switches. Each of these services are indicated schematically by a bi-directional arrow 120 which interconnects a local switch 112 to a lata switch 114, a lata switch to a hub switch 116, and a hub switch to another hub switch.
30 Furthermore, the local switches 112 are connected to a local paging service 118 by a communication link 122 of any conventional nature, including wires connecting the local switch to the local paging service. Each switch is provided with a local telephone trunk 127 which
35 functions as a maintenance port. Furthermore, dotted

bi-directional lines 124 illustrate alternative communication paths between switches which may be used in the case of malfunction or busy conditions. It should be further understood that the network is not limited to any particular communication protocol linking switches, nor connecting the local switch to the local paging service. A telephone trunk 28 functions as an input for manual (telephone handset) and automatic device entry of pages as described below.

The network 110 provides numeric, alphanumeric and data services to all points within the United States and participating countries. In the preferred embodiment of the network, a universal code is used for encoding transmissions of characters over both the communication links 120 and 122 which is compatible with existing analog and digital ~~transmitter~~ ^{transmitters} 115. A universal code discussed in the aforementioned patents utilizes sixteen tones for encoding all characters for transmission between switches or to a local paging service 118. Each character is transmitted as two successive tones. A X.25 modified transmission protocol which is disclosed in the aforementioned network patents is preferably utilized for transmitting packets of pages between switches.

The network 110 is economical to implement and operate as a consequence of utilizing distributed processing technologies and transmission of pages periodically in packets of pages between the switches. Dynamic interaction between a frequency agile pager, which preferably is of the type described in the above-referenced receiver patents and applications and the network 110 efficiently utilizes transmission time that is available in the frequency spectrum. One of the distinct advantages of the network 110 is that it utilizes existing paging common carriers to deliver

9
10
15
20
25
30
35

13

pages to the end user with existing paging RF coverage in the United States being greater than 85% of its geographical area with just two 150 MHz frequencies with a total of 10,500 additional frequencies being available for paging receiver use. Wire line common carriers, private systems, hospital, government, emergency and many other services can be accommodated by the utilization of dynamic frequency programming, by the network 110 to change the frequency band on which individual paging receivers may receive pages.

The network 110 provides an integrated sublocal, local, regional and nationwide paging network that is transparent to use by the subscriber and provides for pages (data transmissions) to be called into an existing local paging service 118 by the making of a local phone call on a telephone trunk 128 connected to the local switch 112 in a conventional fashion as well as to any lata switch 114 throughout the network 110 by a local phone call to telephone trunk 126. The functionality of permitting pages or data transmissions to be originated anywhere within the network 110 by local telephone call, preferably by calling a single number within the country (950-XXXX) avoids the telephone expense and system overhead caused by calling of a central switch to originate a page. It should be understood that the network's usage of periodically transmitting packets of pages between switches results in a much lower cost than the cost of 800 or conventional long distance service. The phone trunk 126 for calling the lata switch 114 to place a page anywhere within the network 110 is indicated by bi-directional arrows to each lata switch. Regardless of the location of the person making the telephone call to a lata switch 114 over telephone trunk 126 to originate a page, the lata switch will formulate a page

14

with the destination specified by geographically descriptive digits of the identification code inputted with the call to request a page or data transmission to the data switch and the network 110 will automatically route the page through the switches of the network to the person being paged by way of the local switch 112, which stores a subscriber file that stores the identification code of the subscriber and paging receiver. The local switch 112, which stores the identification code inputted with the page in its subscriber file, adds one or more destinations to the page and transmits the page(s) to the local paging service 118 and/or the network 110 by way of the data switch 114 having jurisdiction. The person placing the page by calling the local switch 112 on telephone trunk 128 or the data switch 114 on telephone trunk 126 does not have to know the location of the person receiving the page.

The local switch 112 is connected to a participating common carrier paging service 118 located in a particular geographic area. The local switch 112 has local direct inward dial trunks 128 which permits the subscriber to use a local telephone call to place a page. Pages over the local telephone trunks 128 may be (1) numeric characters which are entered manually by DTMF tones or other telephone coding mechanisms, (2) alphanumeric characters which are entered manually by DTMF tones or other coding mechanisms, (3) alphanumeric characters which are entered by an automatic message inputting device using an encoding format having a transmission protocol of conventional nature such as DTMF tones or (4) a high speed (baud rate) encoding protocol such as an X.25 protocol permitting a variable number of pages or data transmissions each with its own network destination to

be formed into a packet which is transmitted to a single switch. The local switch 12 has voice prompting which facilitates the person placing a call on the telephone trunk 28 to enter a message to be transmitted as a page.

5 The local switch 112 processes the pages received from the telephone trunk 128 and from the associated data switch 114 to which the local switch is connected by the communication link 120. It should be understood
10 that the local switch 112 has programming which automatically and dynamically monitors paging traffic when a plurality of transmission frequencies are used and allocates the frequencies available to the paging service 118 for transmission to the paging receivers to
15 maximize the local paging services paging throughput as described below. The local switch 112 calls the resident local paging terminal of the paging service 118 and determines how much air time it has to deliver a batch of pages to the transmitter 115
20 associated with the local paging service. The local switch 112 then calls the local paging terminal of the local paging service 118 and transmits a batch of pages encoded in the hybrid encoding format described below which is compatible with existing analog and digital FM
25 paging transmitters.

The local switch periodically transmits packets of pages or data transmissions stored in an outbound data buffer over communication link 20 to the data
30 switch 114 having jurisdiction over it which provides cost efficient transmission and efficient page or data transmission processing. This architecture is highly efficient in routing the pages originating at the local switch 112 to be transmitted by the network 110 which are intended for broadcast by a transmitter remote from
35 the local switch having a subscriber file storing the

16

identification code of the subscriber to which data or a page is to be transmitted.

When the subscriber desires to receive regional, national, or international service, the local data switch 112 is programmed by the subscriber by simple telephone area code entries which identify the service areas to which pages or data transmissions are to be transmitted. The programming is accomplished by adding or deleting one or more area codes of the subscriber's destination field contained in a subscriber file maintained in the subscriber's local switch 112. In the United States, area codes are used for ease of subscriber use and telephone books may then serve as the service area directory. The same ease of use is available to worldwide customers with county-city code entries available from telephone books in any airport, hotel or business.

The local switch controls the generation of individual pages or data transmissions having message detail as described below with reference to Fig. 6. The number of pages or data transmissions which are generated in response to a page received without an area destination from the telephone trunk 128 or from a data switch 114 is determined by the central processor of the local switch 112 interrogating any area destinations listed in the destination area code field of the local switch as described below with reference to Fig. 3. Each page or data transmission generated by the processor contains the same message content. A separate page or data transmission is generated for each destination area listed in the destination area code field (and) if the local service option of the service option field is selected, as described below, an additional page or data transmission is generated for broadcast by the local

17

paging service 118 without an area destination in the
 network which is processed by the local switch 112 as a
 page or data transmission received from the network for
 broadcast by the local paging service. Furthermore,
 5 each individual page or data transmission generated by
 a local switch 12 contains one or more commands. The
 commands which are added to each page or data
 transmission transmitting a message are determined by
 the operation of the central processor of the local
 10 switch 112 in response to interrogation of the selected
 service options of the subscriber. Programming of
 receivers with the channel programming command is in
 response to the local switch programming the receiver
 to receive one or more channels, subscriber programming
 15 of destination areas of reception in the destination
 area code field, and the degree of utilization of the
 channels of the local transmitter 115.

The central processor of the local switch 112
 processes each individual page or data transmission
 20 received from the network to determine if it originated
 from a local switch 112 or a data switch 114. This
 determination is made by determining if a destination
 header identifying a data switch 114 originating the
 page precedes the paging receiver identification code
 25 in a packet having the configuration of Fig. 6. In the
 absence of the header (which is a geographic
 identification of the originating data switch 112 in
 the network) in an individual page or data
 transmission, the page or data transmission is
 30 processed exclusively by the local switch 112 for
 broadcast by the associated local paging service 118
 without interrogation of a subscriber file in the local
 switch. If the header is found in a page or data
 transmission, the central processor processes the page
 35 as either a request to reprogram the subscriber file or

18

9
 5 as a page received on the telephone port 128 without an area destination which must be processed to determine one or more area destinations and ^{be} formed into new pages each with a different area destination from the area destination field if transmission by the network is to occur and into a page or data without an area destination if transmission by the local service 18 is to occur.

10 The local switch 112 also serves as the dynamic programming interface between the paging or data receivers 119 and the network 110. The local paging service 18 may cause channels to be received by receivers 19, change subscriber identification codes and add new customers to the network 110 utilizing the
 15 local switch 112. The functionality of the receiver 119 can be changed from a fixed channel to a multi-channel or a scanning receiver as required by use of the channel programming command.

20 Messages originating at the local switch 112 which are transmitted to the data collector switch 114 having jurisdiction over it are packetized as described below with reference to Fig. 6. Destination area codes (telephone area codes or other geographically descriptive code) are added to pages or data
 25 transmissions prior to transmission to the data switch 114 and the receiver 119 is dynamically and automatically reprogrammed for the new service areas by the local switch 112 issuing channel programming command(s) which ensures that the receiver 119 is
 30 programmed to receive channels in each designated area. The current channels remain in the receiver 119 to avoid loss of a message while a subscriber is still in the area.

19

The lata switch 114 provides a second tier of network intelligence. This intelligence includes page or data transmission processing, packetizing and routing. The lata switch 114 receives packets of pages from each of the local switches 112 within its jurisdiction as well as the hub switch 116 having jurisdiction over it. The lata switch 114 provides the geographical presence for the network 110 to originate and terminate pages or data transmissions utilizing dial-up or dedicated communication services.

The lata switch 114 is responsible for collection of pages from the local switches 112 within its jurisdiction. When a packet of pages is received from the local switch 112, it is disassembled, processed and stored for transmission to the proper destination(s) in one or more packets each consisting of one or more pages which are intended for destination(s) either within or outside the lata switch jurisdiction. The lata switch 114 periodically transmits packets of pages stored in its outbound hub buffer and its outbound local buffer to the associated hub switch 116 having jurisdiction over it and to local switches 112 within its jurisdiction which provides cost efficient transmission and efficient processing by avoiding processing by a single central switch controlling the network 110. This architecture is highly efficient in routing pages or data transmissions originating within the jurisdiction of the lata switch 114 which are intended for broadcast outside its jurisdiction as well as distributing pages or data transmissions from one local switch 112 to one or more additional local switches within the jurisdiction of the lata switch. If the page or data transmission is destined for distribution within the jurisdiction of the lata switch 114, the page or data transmission is processed

20

into packets for transmission to each of the local switches 112 within its jurisdiction or alternatively to less than all of the local switches in its jurisdiction. The pages or data transmissions are then periodically transmitted as packets to the local switches 112 within the jurisdiction of the data switch 114.

The data switch 114 is also responsible for collection of pages outside its jurisdiction to be broadcast to the local switches 112 within its jurisdiction. Packets received from the hub switch 116 are disassembled, processed, and packetized for transmission to the destination local switches 112.

The function of the data switch 114 in collecting requests for placing pages or data transmissions in the network or to reprogram the subscriber file of a local switch 112 by placing a local phone call on telephone trunk 126 is an important aspect of the network invention. The data switch 114 places the header discussed above, which geographically identifies the data switch originating the page or data transmission in front of the receiver identification code, in a packet as illustrated in the message detail of Fig. 6 to enable the local switch 112 to differentiate between pages or data transmission which are for broadcast by the local service 118 associated with a receiving local switch 112 and pages or data transmission which require access to the subscriber files to generate one or more pages or data transmissions for broadcast or for reprogramming a subscriber file. Preferably, the header is four digits comprised of a country code followed by the telephone area code identifying the data switch 114 which received the call for the originating page or data transmission.

21

The hub switch 116 provides the third tier of network intelligence and serves as an inter-regional communications link. One hub switch 116 will preferably be located in each international region to serve as a network routing switch. In the United States, a hub switch 116 will be located within the region served by each of the Bell regional companies (RBOC's). Accordingly, in the United States the preferred implementation of the network 110 includes seven distinct hub switches 116. Each hub switch 116 in a preferred embodiment can have fifty-five lata switches 114 under its jurisdiction. The hub switch 116 also serves as a network routing switch for inter-hub calls when pages or data transmissions are to continue in the hub-to-hub network.

When a packet of pages is received from either another hub switch 116 or a lata switch 114 within its jurisdiction, the pages or data transmission are disassembled for examination. Each page or data transmission is examined for its destination address(es). A determination is made if the hub switch 116 should forward the page or data transmission to one of the six adjacent hub switches or forward the page or data transmission to a lata switch 114 within its jurisdiction. The pages or data transmissions are then destination processed and packetized for transmission to either another hub switch 116 or a lata switch 114 within its jurisdiction.

22

Fig. 3 illustrates a memory map of the RAM of a local switch 112. The RAM has four main storage areas which are the subscriber files 154, channel files 156, data buffers 158 and local buffers 160.

5 Each local switch 112 is allocated a capacity of, for example, 10,000 subscribers which are identified by a four-digit code stored in field 162 of the subscriber files 154.

10 Field 164 stores the subscriber's local telephone number within the area code serviced by the data switch 114 having jurisdiction.

15 Field 166 is the subscriber's receiver identification code which uniquely identifies the subscriber and the receiver 119 of the subscriber which is to receive pages or data transmissions throughout the network 110. The receiver identification number (code) consists of 8 digits with the four most significant digits geographically representing the area serviced by the associated data switch 114 (country code as the most significant digit followed sequentially by area or city code lesser significant digits) and the four least significant digits being digits assigned to identify 10,000 subscribers within the jurisdiction of the local switch. The capacity of
20 the network 110 is 100 million subscribers with the eight digit identification code. The least significant numbers of the identification code define subscribers of a specific local switch 112 within the jurisdiction of the data switch 114.

25 Field 168 stores the service options which each subscriber may choose to have provided by the local service 118. The service options control the commands, which are used with pages or data transmissions sent to the receivers 119. The main CPU interrogates the particular subscriber file identified by the
30

23

identification code inputted with the request for a page or data transmission by telephone trunks 126 or 128, causes storage of the page or data transmission, determines the destination(s) of the page or data transmission and the appropriate system command to be used to transmit the page or data transmission. It should be understood that the service options may be dynamically programmed through voice prompted communications over the telephone trunk lines 128 with the local switch 112 and through telephone calls to the data switch 114 by trunk 126 as described below.

The service options are described as follows. The service option "a" is for no service which is a condition when an active subscriber does not wish to receive any pages or data transmissions such as may occur when the subscriber is on vacation or is otherwise desirous of not being reached for a period of time but does not wish to be removed from the subscriber base of the system. The service option "b" is for pages or data transmissions to be broadcast only by the transmitter 115 of the local service 118. The service option "c" is for regional service which is for pages or data transmissions to be broadcast throughout all of the local services 118 which are within its data switch jurisdiction. The service option "d" is for national service which is for pages or data transmissions to be broadcast from the local switch 112 to one or more data switches 114 other than the data switch having jurisdiction over the local switch. While not illustrated, an international service option may be added. The service option "e" is for a repeat of pages or data transmissions for any of the "b", "c" or "d" service options so that a page or data transmission is broadcast more than once. The service option "f" is for data service which causes the page or

24

data transmission to be stored in a specified section of the receiver memory. The service option "g" is for external data service which commands the receiver 119 to output the page or data transmission to the external data port of the receiver. This option permits the receiver 119 to support peripheral devices such as printers or processors to provide a wide range of data services.

The following additional fields are provided. The fifth field 170 is the subscriber's name and the subscriber's specified account number. The sixth field 172 is the subscriber's account number entry for purposes of interval billing by the local service 118. The seventh field 174 is the subscriber's count (local, regional or national) which is a total of the number of pages or data ~~transmission~~ made in a billing period. The eighth field 176 is the total number of data characters sent during the billing period.

The ninth field 178 is the destination (area code(s)) of each of the pages or data transmissions. For local service, there is no area code specified. For regional service, the area code of the associated lata switch 114 having jurisdiction over the local switch 112 is specified and for national and international service, one or more area codes or other geographic identification identifying lata switches other than the lata switch having jurisdiction over the local switch are specified. For international service, a country code may be used to identify lata switches 114 within a particular country. Any number of area codes may be specified but in a preferred embodiment of the network 110, three area codes is a maximum number of lata switches 114 which may be specified as regions to receive pages from the local switch 112.

25

The above-referenced description describes the first file of the n (10,000) possible subscriber files stored in the subscriber files 154. It should be understood that the other subscriber files have the same configuration. Access to the subscriber file is obtained by a voice prompted message requiring the inputting of a secret code which if inputted correctly is followed by voice prompted requests requesting specification of the information of the subscriber file to be changed.

The frequency files 156 perform an important function in the network 110. The frequency files 156 contain n possible lata files with each individual file identifying up to, for example, 15 four-digit numbers that represent broadcast channels available within the service area of a lata switch 114. Thus, each of the individual lata switches 114 in the network 110 will have a separate frequency file which identifies all of the channels which are available to transmit pages or data transmissions from the transmitters 115 associated with the local services 118 under the jurisdiction of that lata switch 114. The channels are stored as a four-digit number in a hexadecimal numbering system which requires only four digits of space. A file containing all zeros (no channel) will cause an invalid area code message to be returned to a subscriber attempting to reprogram service areas. The frequency files are the source of channels which are utilized by the channel programming command to program each receiver 119 for operation in each lata switch jurisdiction and the local switch jurisdiction. For example, a receiver 119 which is to be serviced by only a single local service 118 may be programmed to receive only a single or a number of channels up to the number of channels used by that local paging service.

26

Furthermore, for regional service or national service, the frequency files 156 are used to program the receiver 119 to receive pages or data transmissions from the channels used by the local services 118 within the designated area codes representative of the service areas serviced by the lata switches 114. Furthermore, if a receiver 119 is to be programmed to receive messages in a particular area serviced by a lata switch 114 as a consequence of the subscriber travelling, the channel programming command utilizes the channels stored in the file number corresponding to the jurisdiction of the lata switch 114 in the area to which the subscriber is to travel, to dynamically program the channel(s) which the paging receiver is to receive in that area. For service in a local region, the frequency files are used as a source of channels to be used by the channel programming command to dynamically shift the channels on which the paging receiver is to receive a page, to adjust the channels used in the broadcast area used by the local service 118 associated with the local switch 112 based on the amount of traffic on each channel and to further provide a source of channels which are to be used for specialized services for transmitting particular types of information to particular subscribers such as, but not limited to stock quotations.

The lata buffers 158 consist of an inbound lata buffer 180 and an outbound lata buffer 182. The inbound lata buffer 180 functions to receive pages or data transmissions coded in ASCII which have been processed to strip the X.25 transmission protocol used for transmitting pages from the lata switch 114 to the local switch 112 and converted from the hybrid code described below to ASCII. Pages or data transmissions which are initially stored in the inbound lata

27

buffer 180 are processed for destination and are either for broadcast by the associated local service 118 in which case they are ultimately stored in the appropriate identification code buffer 186 which matches the least significant digit of the identification code contained with the page or data transmission or in the outbound data buffer 182 if the page or data transmission originated from one of the data switches 114 by calling on the telephone trunk 126 and which has a final destination which is determined by the field 178 of the subscriber file 154.

The local buffers 160 are comprised of an inbound buffer 184 for receiving all local inbound pages or data ^{transmission} ~~transmission~~ which originate from the trunk line 128 which is connected to the local switch 112 and a plurality of identification code buffers 186 which are each individually assigned to store outbound pages or data transmissions with a particular least significant identification code digit of the number base used for the subscriber identification code which are to be transmitted to a receiver 119. All of the received pages or data transmissions from the local switch 112 are initially stored in the buffer 184. Each of the individual identification code buffers 186 stores pages or data transmissions for broadcast by the local service 118 in batches which are grouped by the least significant digit of the subscriber identification code received with the page or data transmission after sorting by the CPU. In other words, the least significant digit of the subscriber identification code within a page or data transmission for broadcast by a local service 118 determines in which of the identification code buffers 186 the page or data transmission is stored. For example, if the last digit of the identification code of a page or data

28

transmission for broadcast by the local service 118 ends in the digit 0, the page or data transmission is stored in the identification code buffer identified by "0".

5 Fig. 4 is a memory map of the random access memory of the data switch 114. The random access memory has three main areas and two optional areas. The three main areas are hub buffers 188, local buffers 190 and a data identification code (ID) memory 192. The optional
10 memory areas are an all call buffer 194 for storing nationwide pages or data transmissions received from the hub switch 116 which are to be transmitted to all of the local switches 112 under the jurisdiction of the data switch 114 and an all call buffer 196 which stores
15 pages or data transmissions received from one of the local switches 112 which are to be transmitted to all of the local switches under the jurisdiction of the data switch 114.

 The hub buffers 188 are an outbound hub buffer 198
20 and an inbound hub buffer 200. The outbound hub buffer 198 stores pages or data transmissions to be periodically transmitted to the hub switch 116 having jurisdiction over the data switch 114 under the control of the CPU. The inbound hub buffer 200 stores pages or
25 data transmissions which are periodically received from the associated hub switch 116 via storage in a buffer of the CPU.

 The local buffers 190 are comprised of an inbound local buffer 202 which stores groups of inbound pages
30 or data transmissions received from the local switches 112 and a plurality of outbound local buffers 204 each of which store groups of pages or data transmissions which are to be transmitted periodically to a specific one of the local switches with a separate
35 outbound local buffer being provided for each of the

29

a
 local switches under the jurisdiction of the lata switch 114. The CPU processes each of the pages or data ~~transmission~~ ^{transmission} which is received in the inbound buffers 200 and 202 by destination and causes storage in the outbound buffers 198 and 204 which is associated with the destination of the page or data transmission.

5 The lata identification code memory 192 stores the subscriber identification numbers of all of the subscribers which are associated with each of the local
 10 switches 112 within its jurisdiction. The lata identification code memory 192 is used for determining the local switch 112 which stores a subscriber file of the subscriber used for pages or data ~~transmission~~ ^{transmission} which are inputted to the system from a direct call by
 15 telephone trunk 126 to a lata switch 114 or from a direct call by telephone trunk 126 to a lata switch by a subscriber to program the reception area of pages or data transmissions by changing the destination 178 of the pages or data transmissions. The lata
 20 identification code memory 192 may be organized by subscriber identification codes which are within the jurisdiction of each local switch 112 so that the matching of an identification code of a page or data transmission inputted to the lata switch 114 in the
 25 lata identification code memory 192 provides the location of the particular local switch which stores the subscriber file 154 of that subscriber.

In order to avoid having to provide additional storage space in each of the outbound local
 30 buffers 204, the optional all call buffer 194 may be provided to store a single page or data transmission, received from the hub switch 116 having jurisdiction over the lata switch 114, which is to be transmitted to each of the local switches 112. Similarly, the
 35 optional all call buffer 196 may be provided for

30

receiving pages or data transmissions from an individual local switch 112 which are to be transmitted to all of the local switches within the jurisdiction of the lata switch 114.

5 For pages, data transmissions or requests to reprogram the subscriber file 154 which are made to a lata switch 114 over telephone trunk 126 which require access to a subscriber file outside the jurisdiction of the lata switch, the CPU forms a page or data
10 transmission contained in a packet having an area destination identified by the four most significant digits of the identification code inputted to the lata switch 114 preceded by the identification code of the receiver 119 to receive the page or data transmission,
15 preceded by the geographical area identification of the lata switch receiving the call to originate a page or data transmission or to program the subscriber file which is transmitted by the network 110 to the specified area destination. For pages or data
20 transmissions to be billed to subscribers stored in the subscriber file 154 of a local switch 112 within the jurisdiction of the lata switch 114 or requests to program the subscriber file 154, the CPU forms a packet having an area destination of the local switch 112
25 within its jurisdiction which stores the subscriber identification code as determined by interrogation of the lata identification code buffer 192 by the CPU. The ultimate destination of a page or data transmission is determined by the destination field 178 of the
30 subscriber file 154 matching the identification code of the receiver 119 either within or outside the jurisdiction of the lata switch that is called in over telephone trunk 126. The local switch 112 containing the subscriber file 154 creates the one or more pages or data transmissions in accordance with the
35

31

information in the subscriber file including the adding of destination(s) and the appropriate command. Transmission of the pages or data transmissions created by the local switch 112 in response to a call to a data switch 114 is identical to the transmission of pages or data transmissions originating at the local switch 112 by the placing of a telephone call on telephone trunk 128. In the case of requesting programming of the subscriber's file 154, the caller must in response to a voice prompted message enter a four-digit secret identification code to obtain access to the subscriber file with voice prompted messages being supplied under the control of the CPU to control the input of programming information from the subscriber. To request a page or data transmission by calling the data switch 114, the caller will receive a voice prompted message to enter the subscriber identification code and then the appropriate page or data transmission.

Fig. 5 is a memory map of the random access memory of the hub switch 116. The hub switch memory map is comprised of four main parts which are hub buffers 206, data buffers 208, data code tables 210 and hub routing codes 212. The hub buffers 206 are comprised of a plurality of inbound hub buffers 214 which correspond in number to the number of other hub switches 116 in the network 110 which have direct connection to the hub switch and a corresponding number of outbound hub buffers 216. The individual inbound hub buffers 214 each store pages or data transmissions received from one of the hub switches 116 with pages or data transmissions received from each adjacent hub switch 116 being stored in only a single one of the inbound hub buffers 214. Similarly, pages or data transmissions which are to be transmitted to another hub switch 116 are stored in the outbound hub

32

buffer 216 which is associated with the destination hub switch to which they are being transmitted with all pages or data transmissions which are to be routed to a single hub switch being stored in a corresponding one of the outbound hub buffers 216 with a separate hub buffer being associated with each hub switch to which pages or data transmissions are directly transmitted. The data buffers 208 are comprised of a plurality of inbound data buffers 218 which correspond to the number of data switches 114 under the jurisdiction of the hub switch 116. The inbound data buffers 218 store all of the pages or data transmissions received from the data switches 114 under the jurisdiction of the hub switch 116. The outbound data buffers 220 correspond in number to the data switches 114 under the jurisdiction of the hub switch 116 with a separate data buffer being associated with each of the data switches. The outbound data buffers 220 store groups of pages or data transmissions to be periodically transmitted to their associated data switch 114. Pages or data transmissions which are stored in the inbound hub buffers 214 are processed by destination by the CPU and stored in either the outbound hub buffer 216, which is the destination of the pages or data transmissions not to be received by a data switch 114 under the jurisdiction of the hub switch 116, or in one or more of the outbound data buffers 220 if the destination of the packets received from another hub switch 116 is a data switch under the jurisdiction of the hub switch. The CPU also processes the pages or data transmissions stored in the inbound data buffers 218 according to their destination and causes their storage in either the outbound hub buffers 216 if the pages or data transmissions are to be sent to a data switch 114 outside of the jurisdiction of the hub switch 116 or to

33

one or more of the outbound lata switches 220 if the pages or data transmissions are to be received by one or more lata switches 114 under the jurisdiction of the hub switch 116.

5 The lata code tables 210 store each of the lata (telephone area or other geographic identifier) codes 222 under the jurisdiction of the hub switch 116 which are utilized by the comparison performed by the CPU with the pages or data transmissions stored in the
10 inbound hub buffers 214 and inbound lata buffers 218 to determine in which of the outbound hub buffers 216 or outbound lata buffers 220 the pages or data transmissions should be stored. Each separate lata code 222 corresponds to the geographical identification
15 of the lata switch 114 which in the preferred embodiment is the telephone area code of a lata switch's jurisdiction.

 The routing codes 212 determine the transmission routes to other hub switches on a priority basis to
20 which a packet should be sent which are not intended for a lata switch 114 within the jurisdiction of the hub switch 116. It should be understood that a number of factors may be considered in choosing the priority of a route to be used to transmit a packet from one hub
25 switch 116 to another hub switch. It would appear on first analysis that a direct first hub switch to second hub switch route would be best but often the switching overhead of routing a packet through one or more intermediate switches is more than compensated for by
30 the efficiency of a route having one or more intermediate hub switches by adding additional pages or data transmissions to the packet which are inputted to the one or more intermediate hub switch(es) to the packets being transmitted to the second hub switch.
35 The CPU compares the destination of the groups of pages

34

or data transmissions stored in the inbound hub buffers 214 and the inbound data buffers 218 to determine if these pages or data transmissions should be routed to another hub switch 116. The hub routing codes 212 are referred to by default when a match is not found by the CPU in comparing the destination of the pages or data transmissions stored in the inbound hub buffers 214 and inbound data buffers 218 with the codes stored in the data code tables 210. Each page or data transmission stored in the inbound hub buffer 214 and inbound data buffers 218 is processed by destination by the CPU and caused to be stored in the outbound buffers 216 and 220 which correspond to its destination. Each individual hub routing code contains the hub switch destination priorities for pages or data transmissions to be sent to a single data switch 114 outside the jurisdiction of the hub switch 116. For example, for the data switch 114 having jurisdiction over area code 312, the hub routing code 234 determines the priorities in descending order from the highest priority to the lowest priority such that the highest priority hub would be #1 followed by #2-#6.

Fig. 6 illustrates a preferred transmission protocol to be used for transmitting packets between switches. The protocol which is used is a modified X.25 protocol. As illustrated, each packet contains five separate layers. The first layer is the destination telephone number which is the receiving port to receive the page or data transmission. With reference to Fig. 2 if a packet of X.25 formatted pages or data transmissions were to be sent from a first data switch 114 to its associated hub switch 116 over communication path 120, the destination telephone number would be the telephone number of the hub switch. It should be further understood that the X.25

35

35

transmission protocol as described herein may be utilized with other types of communication mediums between switches such that a destination telephone number may be replaced with another form of address of the receiving switch. The second layer indicates the packet size field in terms of succeeding layers of information. In the present case levels 3, 4 and 5 are provided which dictates that the packet size would store the number 3 to indicate the subsequently lower third, fourth and fifth layers. The third layer contains an origination switch address and a destination switch address which can be either telephone numbers or real addresses within the network 110. The fourth layer is the number of pages or data transmissions which are contained in a packet. As illustrated, this number may be any integer n. The fifth layer is one or more pages or data transmissions which each correspond to an individual page or data transmission to be sent to a particular receiver 119.

Each message includes the following information. In accordance with standard X.25 protocol, a beginning of file header is included. Following the beginning of file header is a receiver I.D. code which is the identification code of the destination receiver which is identical to the subscriber identification code stored in the subscriber files 154 of the subscriber to receive the page or data transmission. Following the I.D. code is the destination(s) of the page or data transmission which is geographically descriptive of the area to which the page or data transmission is to be transmitted and is added by the local switch 112 interrogating the destination field 178 of Fig. 3. In the preferred embodiment, the destination is a combination of country and area code as utilized by the telephone system to identify the area to which the page

SECRET 000000

36

or data transmission is destined. For each country, the same country code will be used so that if the system 110 as illustrated in Fig. 1 were to be utilized for the United States, the first digit of the destination would be a 1. Similarly, the destinations in other countries would be followed by different numbers identifying those countries followed by code which breaks up the identified country into smaller geographic regions. ~~While the utilization of area codes under the telephone system facilitates the usage of the present invention, it~~ should be understood that a destination which is not based on the telephone system is equally usable ~~with the present invention~~. The field of special commands are the system commands which are transmitted with each page or data transmission to a receiver. The "page" or "data transmission" is the part which is to be displayed to the bearer of the receiver 119 and may be numeric or alphanumeric characters. The end of the file and file size information are part of a standard X.25 protocol.

Fig. 7 illustrates an interconnection between a paging receiver (left side) in accordance with the above-referenced receiver patents and a printer (right side) which has been offered for sale by Telefind Corporation of Coral Gables, Florida. The "EXTERNAL ANTENNA" pin is for connection only to an external antenna and connects the RF signal from the external antenna to the receiver internal antenna. The "LINK" pin is detected by the printer to determine if the receiver 119 is connected or not. If the receiver is not connected when peripheral power is on, then the CPU of the printer will detect that the "LINK" pin is high. Otherwise the "LINK" pin will be low. The pin "EXTERNAL BUZZER" outputs a 2KHz trigger signal when a page or data transmission is received. The

37

"EXTERNAL BUZZER" pin also outputs the 2KHz trigger signal when display of a message is complete. The pin "PRG VCC" is supplied 5 volt power by the attached printer to provide power to the receiver 119 whether the pager is powered or not. The "GROUND" pin is ground for the printer and receiver 119. The pin "BUSY" is pulled high by the printer if the printer is too busy to handle input data bits on the "PRTDATA" pin of the receiver 119. The "PRTDATA" pin is the data output from the receiver 119 to the printer. Serial data bits are fed to the printer to drive the printer to generate text corresponding to the data bits. The "DIS AUDIO" pin provides external audio which may be the X.25 modified protocol of Fig. 6 encoded into audio tones which modulate the channel carrier on which information is received by the receiver ¹¹⁹~~19~~. When the "DIS AUDIO" pin is high, it indicates that the display button is pressed. The memory of the receiver 119 stores the text to be printed by the printer. The text is downloaded through the aforementioned interconnection upon connection to the printer to generate a hard copy of the text stored in the memory.

38

Disclosure of Invention

a

5 The present invention provides an integration of an electronic mail system with an RF information transmission network for transmitting electronic mail originating at processors either within or outside an electronic mail system by RF communication to at least one destination processor within an electronic mail system by a RF receiver which ^{transfer} relays the information to the destination processor and method of use thereof.

10 The RF receiver stores the received information which is to be relayed to the destination processor. Storage in the RF receiver memory permits the reception of the information without a connection of the RF receiver to the destination processor thus eliminating the requirement that the destination processor is turned on and carried with the user of the destination processor.

15 In a typical application with a portable PC functioning as the destination processor, it is important that reception of the information by the RF receiver does not require the drawing of power from the PC battery.

20 The RF receiver automatically relays the information to the destination processor upon connection of the RF receiver to the destination processor. The destination processor may be within the same electronic mail system containing the originating processor which originated the information or another electronic mail system. While a preferred application of the invention is with portable destination processors, it should be understood that the originating and destination

25 processors may be at a fixed site or portable. The use of the RF receiver to receive electronic mail permits fixed site destination processors to receive electronic mail without calling the electronic mail system as in the prior art by using the storage of the RF receiver which may be carried on the user of the destination

30

35

processor either within an office or other site or for travel. The RF receiver provides the automatic storage of electronic mail and review of its content without interaction with the destination processor. The stored
5 messages may be transferred at a later time automatically without manually keying the message which is an important consideration in using portable PCs. The problems of the prior art in delivering electronic mail to destination processors within an electronic
10 mail system which are being exacerbated by the increasing portability of personal computers and the absence of a current system for delivering electronic mail between electronic mail systems are overcome by the present invention.

15 The present invention transmits electronic mail from an originating processor to at least one destination processor through an interface switch. The interface switch connects an electronic mail system and/or at least one additional processor to ^a RF data
20 transmission network which transmits the information to a RF receiver which is connectable to the destination processor to ^{transfer} ~~relay~~ the received RF message from the RF receiver to the destination processor.

25 The invention is user friendly in that the minimum amount of information which must be provided to initiate the transmission of electronic mail from an originating processor to at least one destination processor is an identification of the destination
30 processor and information indicating that the message is to be sent by the RF information transmission network. The inputting of information that the information is to be sent by the RF information transmission network may be simplified to the extent that an icon driven display associated with the
35 originating processor, such as a mouse, may be used to

9
a

40

point to an icon of a radio receiver. Alternatively, an identification of the address of the interface switch through which the information is transmitted to the RF transmission network may be inputted by the operator or a machine operating the originating processor. Finally the entering of the destination processor identified in terms such as the user's name may be entered which is compared with a look up table to determine if a match exists. If a match exists, the matched identification of the destination processor supplies an address of the interface switch and an identification of ^a RF receiver to receive the information and ~~relay it~~ ^{transfer the information} to the destination processor. The inputting of the destination processor in terms such as the user's name to an originating processor may be used by the destination processor, gateway switch or addressed interface switch to look up an identification number of the RF receiver within the RF information transmission network which is connectable to the destination processor which is added to the information for use by the RF information transmission network. The electronic mail system or the interface switch may append the identification number of the RF receiver to receive the information which is utilized by the RF information transmission network to determine the final destination of the RF receiver to which the message is broadcast by the RF information transmission network. The appending of the identification number of the RF receiver to the information to be broadcast to the destination processor may be inputted by an operator of the originating processor, added to the information by a comparison of the identification of the destination processor to stored identifications of destination processors stored by the originating processor to which RF messages are to be broadcast by

2025-11-11 14:11:11

41

the RF information transmission network to identify the identification number of the RF receiver in the RF information transmission network, or by a gateway switch in the electronic mail system or the interface switch between the electronic mail system and the RF information transmission network.

The intelligence for determining the identification number of the RF receiver to receive the information is less expensive and operates most efficiently when placed within the interface switch where the aforementioned matching may be produced without requiring modification of either individual originating processors within the electronic mail system or gateway switches within the electronic mail system which have additional functions for supporting other conventional aspects of electronic mail. However, the determination of an identification number of the RF receiver which ^{transfers} relays the information to the destination processor may be located anywhere between the originating processor and the RF information transmission network for practicing the present invention. Similarly, the appending of the address of the interface switch to which the information is transmitted by the electronic mail system for entry into the RF information transmission network for broadcast to the RF receiver for ^{transfers} relaying to the destination processor may be located within any one of the originating processor, gateway switch or interface switch.

~~An electronic mail system for transmitting information from one of a plurality of originating processors to at least one of a plurality of destination processors in accordance with the invention includes at least one gateway switch, a gateway switch storing information received from one of the at least~~

999999
42

one originating processor prior to transmission of the information to the at least one destination processor; an RF information transmission network for transmitting stored information received from one of the at least one gateway switch by RF transmission to at least one destination processor; at least one interface switch, an interface switch connecting a gateway switch to the RF information transmission network and transmitting stored information received from one of the at least one gateway switch to the RF information transmission network; and wherein the information is transmitted to a receiving interface switch by the electronic mail system in response to an address of the receiving interface switch which has been added to the information originated by the originating processor by either the originating processor or gateway switch and the information is transmitted from the receiving interface switch to the RF information transmission network with an address of the destination processor to receive the information which has been added by either the originating processor, a gateway switch or the receiving interface switch. The destination processors may be transported during operation by a user. The receiving interface switch removes information added by the electronic mail system to the information originated by the originating processor from the stored information received from one of the at least one gateway switch and adds information used by the RF information transmission network during transmission of the information to the information originated by the originating processor to an RF receiver in the RF information transmission network which receives the information and relays the information originated by the originating processor to the destination processor.

The RF receiver may be detached from the destination processor during reception of the information with a memory of the RF receiver storing the information. Storage in memory permits review of the information prior to transferring the information to the destination processor by connection the RF receiver to the destination processor. The address of the destination processor is preferably an identification of a RF receiver in the RF information transmission network which receives the information and relays it to the destination processor.

The receiving interface switch stores information which has been stored by at least one gateway switch that is received from a plurality of originating processors, assembles the information from a plurality of originating processors into a packet and transmits the packet to the RF information transmission network. The RF information transmission network comprises a switch which receives the packet from the receiving interface switch and disassembles the packet into information from the plurality of originating processors. The RF information transmission network transmits the disassembled information, including the identification number of the RF receiver, to a switch in the RF information transmission network storing a file identified by the identification number and any destination of the RF receiver in the RF information transmission network to which the information and identification number is to be transmitted by the RF information transmission network. The switch adds any destination of the RF receiver to the information and the RF information transmission network in response to any added destination transmits the information and identification number to the destination for

RF broadcast to the RF receiver for relaying to the destination processor.

5 The electronic mail system also transmits information between an originating processor and at least one destination processor through either a public switch or a private switch telephone network without transmission by the RF information transmission network. The destination processor is addressed by a
10 different address during transmission to the destination processor when using the public or private switch telephone network than during transmission by the RF information transmission network.

15 The RF receiver is connectable to the destination processor and in response to connection of the RF receiver to the destination processor the RF receiver transfers information stored in a memory of the RF receiver received from the originating processor to the destination processor. The number of
20 originating processors is greater than a number of interface switches. The plurality of originating processors also function as destination processors with a RF receiver coupled thereto.

25 The address of the receiving interface switch may be added to the information originated by the originating processor by a gateway switch. The address of the receiving interface switch may be added by the gateway switch by matching an identification of the destination processor such as a name of a user of the destination processor with a stored identification of a
30 destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

The address of the receiving interface switch may also be added by the originating processor. The address of the receiving interface switch may be added by an inputting of the address of the receiving interface switch along with an identification of the destination processor by an operator or a machine using the originating processor or by matching an identification of the destination processor, such as the name of the user, with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

The address of the destination processor, which preferably is an identification number of a RF receiver receiving the information and relaying the information to the destination processor, may be added to the information originated by the originating processor by an operator or a machine using the originating processor. The identification number may also be added to the information originated by the originating processor by matching an identification of the destination processor, such as a user of the destination processor, with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

The address of the destination processor may also be added to the information originated by the originating processor by the gateway switch. The identification number may be added by the gateway switch by matching an identification of the destination processor, such as a name of a user of the destination processor, with a stored identification of a

~~destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.~~

- 5 ~~The address of the destination processor may also be added to the information originated by the originating processor by the receiving interface switch. The identification number may be added by the receiving interface switch to the information~~
- 10 ~~originated by the originating processor by matching an identification of the destination processor, such as a name of a user of a destination processor, with a stored identification of the destination processor and adding an identification number stored with the matched~~
- 15 ~~identification of the destination processor to the information as the identification number.~~

add
at

Brief Description of Drawings

Fig. 1 illustrates a prior art electronic mail system.

- 20 Fig. 2 illustrates a prior art paging system used by the present invention.

Fig. 3 illustrates a memory map of the local switch of the prior art paging system of Fig. 2.

- 25 Fig. 4 illustrates a memory map of a lata switch of the prior art paging system of Fig. 2.

Fig. 5 illustrates a memory map of a hub switch of the prior art paging system of Fig. 2.

Fig. 6 illustrates a message format utilized by the prior art paging system of Fig. 2.

- 30 Fig. 7 illustrates a prior art connection between a receiver in the paging system of Fig. 2 and a printer.

43

Fig. 8 illustrates a block diagram of an electronic mail system in accordance with the present invention.

5 Fig. 9 illustrates a block diagram of the connection of a plurality of electronic mail systems through a plurality of interface switches to an input port of an RF information transmission network utilized by the present invention.

10 Fig. 10 illustrates a block diagram of the transmission of information originating from a plurality of electronic mail systems to a RF information transmission network to a plurality of destination processors and originating processors within a plurality of electronic mail systems in
15 accordance with the present invention.

Fig. 11 illustrates possible distributed functions for performing data processing steps necessary to transmit information from an originating processor to a destination processor using RF transmission in
20 accordance with the present invention.

Fig. 12 is a block diagram of an interface switch in accordance with the present invention.

Best Mode for Carrying Out the Invention

Figs. 8-10 illustrate a block diagram of an electronic mail system 100 which has been integrated with an RF information transmission network 302 for transmitting information from an originating processor within the electronic mail system to a destination processor within the electronic mail system utilizing RF communications in accordance with the present invention. Like reference numerals identify like parts in Figs. 1-10 and 12. The integrated system 100 differs from the prior art of Figs. 1-7 in that the originating processor, which may be any of the processors within computing systems #1-#N is provided the option of transmitting electronic mail (information) to at least one destination processor which may be any processor A-N within the processing systems #1-#N by means of an RF information transmission network 302 as described below. It should be understood that the present invention is not limited to the block diagram form of Figs. 8-10 and 12. Additionally, the communications between the originating processors, gateway switches 14 and destination processors may be through either a public or private switch telephone network ³¹⁴~~104~~ and are not limited to any type of telephone system interconnection. The RF information transmission network 302 functions to transmit the information which originated from ^{one of} the originating ^{processors}~~processors~~ A-N within any of the computing systems #1-#N to the destination processor A-N within any of the computing systems #1-#N by an RF transmission to an RF receiver 119. The RF receiver 119 is connected to the destination processor with the same connections as illustrated in the prior art of Fig. 7. * Upon connection, the receiver 119 relays the information from the RF receiver to the

* WHEN THE RF RECEIVER 119 IS CONNECTED TO THE SAFARI ^{COMPUTER} COMPUTER, THE CONNECTION IS POWERED BY THE SAFARI COMPUTER. TJC 5-17-91

45

destination processor. An important aspect of the present invention is that reception and review of electronic mail can be performed without connection of the RF receiver 119 to the destination processor A-N which permits the receiver to function as a mobile electronic mail receiver. As a result, the user may move from the site of the destination processor A-N either within an office or other location or during travel while receiving electronic mail which was not possible with the prior art. Furthermore, the connection of the RF receiver 119 to the destination processor automatically transfers the electronic mail stored within the memory of the RF receiver to the destination processor without manual keyboarding. A computer program for controlling the transfer of information from the receiver 119 to a SAFARI™ laptop computer of AT&T Corporation is contained within the attached Appendix at pages 1-9. This program automatically provides transfer of the stored electronic mail stored within the memory of the RF receiver 119 into the destination processor A-N where it is accessible to application programs within the destination processor. As a result, the deficiencies of the prior art in requiring substantial expense consequent from the making of telephone calls, substantial labor resultant from the lost time of persons making telephone calls and the inability to deliver electronic mail messages and the more difficult problem of delivering electronic mail messages to portable processors is overcome. Moreover, as is explained in detail below in conjunction with Fig. 11, the initiation of an information transmission from an originating processor A-N to a destination processor A-N using an RF transmission by the RF information transmission network 302 to an individual RF receiver

46

has many different options which are user friendly. The initiation of the transmission of information from an originating processor A-N ^{RF transmission by} to a destination processor A-N using ~~the RF transmissions~~ of the RF information transmission network 302 only requires the identification of an address of the RF receiver, which preferably is the identification number of the receiver 119 in the RF information transmission network and the designation of an address of an interface switch in the form of an address such a "TF MOBOX" which connects the electronic mail system to the RF information transmission network as described below in conjunction with Figs. 9 and 10. The initiator of an electronic mail message, in the most user friendly form of the invention, is only required to input into the originating processor A-N an identification of the destination processor A-N which typically is in the form of a name such as "John Doe". The distributed intelligence of the system implementing the present invention, which may be located in any one of the originating ^{processors} ~~processor~~ A-N, gateway switch 14 or interface switch 304 or distributed therebetween as described below with reference to Fig. 11, may be used to add the necessary address of the interface switch connecting the electronic mail system 1-N to the RF information transmission network 302 and the identification of the RF receiver 119 in the RF information transmission network from the inputting of only an identification of the destination processor A-N. The addition of the identification number of the RF receiver 119 and the address of the interface switch may be implemented by the originating processor A-N of one of the computing systems #1-#N, a gateway switch 14 or an interface switch 304 as described below with reference to Fig. 9.

111-112-113-114-115-116-117-118-119-120-121-122-123-124-125-126-127-128-129-130-131-132-133-134-135-136-137-138-139-140-141-142-143-144-145-146-147-148-149-150-151-152-153-154-155-156-157-158-159-160-161-162-163-164-165-166-167-168-169-170-171-172-173-174-175-176-177-178-179-180-181-182-183-184-185-186-187-188-189-190-191-192-193-194-195-196-197-198-199-200-201-202-203-204-205-206-207-208-209-210-211-212-213-214-215-216-217-218-219-220-221-222-223-224-225-226-227-228-229-230-231-232-233-234-235-236-237-238-239-240-241-242-243-244-245-246-247-248-249-250-251-252-253-254-255-256-257-258-259-260-261-262-263-264-265-266-267-268-269-270-271-272-273-274-275-276-277-278-279-280-281-282-283-284-285-286-287-288-289-290-291-292-293-294-295-296-297-298-299-300-301-302-303-304-305-306-307-308-309-310-311-312-313-314-315-316-317-318-319-320-321-322-323-324-325-326-327-328-329-330-331-332-333-334-335-336-337-338-339-340-341-342-343-344-345-346-347-348-349-350-351-352-353-354-355-356-357-358-359-360-361-362-363-364-365-366-367-368-369-370-371-372-373-374-375-376-377-378-379-380-381-382-383-384-385-386-387-388-389-390-391-392-393-394-395-396-397-398-399-400-401-402-403-404-405-406-407-408-409-410-411-412-413-414-415-416-417-418-419-420-421-422-423-424-425-426-427-428-429-430-431-432-433-434-435-436-437-438-439-440-441-442-443-444-445-446-447-448-449-450-451-452-453-454-455-456-457-458-459-460-461-462-463-464-465-466-467-468-469-470-471-472-473-474-475-476-477-478-479-480-481-482-483-484-485-486-487-488-489-490-491-492-493-494-495-496-497-498-499-500-501-502-503-504-505-506-507-508-509-510-511-512-513-514-515-516-517-518-519-520-521-522-523-524-525-526-527-528-529-530-531-532-533-534-535-536-537-538-539-540-541-542-543-544-545-546-547-548-549-550-551-552-553-554-555-556-557-558-559-560-561-562-563-564-565-566-567-568-569-570-571-572-573-574-575-576-577-578-579-580-581-582-583-584-585-586-587-588-589-590-591-592-593-594-595-596-597-598-599-600-601-602-603-604-605-606-607-608-609-610-611-612-613-614-615-616-617-618-619-620-621-622-623-624-625-626-627-628-629-630-631-632-633-634-635-636-637-638-639-640-641-642-643-644-645-646-647-648-649-650-651-652-653-654-655-656-657-658-659-660-661-662-663-664-665-666-667-668-669-670-671-672-673-674-675-676-677-678-679-680-681-682-683-684-685-686-687-688-689-690-691-692-693-694-695-696-697-698-699-700-701-702-703-704-705-706-707-708-709-710-711-712-713-714-715-716-717-718-719-720-721-722-723-724-725-726-727-728-729-730-731-732-733-734-735-736-737-738-739-740-741-742-743-744-745-746-747-748-749-750-751-752-753-754-755-756-757-758-759-760-761-762-763-764-765-766-767-768-769-770-771-772-773-774-775-776-777-778-779-780-781-782-783-784-785-786-787-788-789-790-791-792-793-794-795-796-797-798-799-800-801-802-803-804-805-806-807-808-809-810-811-812-813-814-815-816-817-818-819-820-821-822-823-824-825-826-827-828-829-830-831-832-833-834-835-836-837-838-839-840-841-842-843-844-845-846-847-848-849-850-851-852-853-854-855-856-857-858-859-860-861-862-863-864-865-866-867-868-869-870-871-872-873-874-875-876-877-878-879-880-881-882-883-884-885-886-887-888-889-890-891-892-893-894-895-896-897-898-899-900-901-902-903-904-905-906-907-908-909-910-911-912-913-914-915-916-917-918-919-920-921-922-923-924-925-926-927-928-929-930-931-932-933-934-935-936-937-938-939-940-941-942-943-944-945-946-947-948-949-950-951-952-953-954-955-956-957-958-959-960-961-962-963-964-965-966-967-968-969-970-971-972-973-974-975-976-977-978-979-980-981-982-983-984-985-986-987-988-989-990-991-992-993-994-995-996-997-998-999-1000

47

Fig. 9 illustrates a block diagram of the connection between a plurality of gateway switches with mailboxes 14 in different electronic mail systems to the RF information transmission network 302. It should be understood that multiple gateway switches with mailboxes 14 from a single electronic mail system 1-N may be connected to each interface switch 304 instead of the connection of a single gateway switch with mailbox to a single interface switch as illustrated. A plurality of interface switches 304 connect information transmitted from at least one electronic mail system as illustrated in Fig. 8, but *optionally*, a plurality of electronic mail systems 1-N each as illustrated in Fig. 8 are connected to a data input port of the RF information transmission system ~~as illustrated in Fig. 12~~ which is preferably hub switch 116 of the prior art paging network described above with reference to Figs. 2-6. The dotted line communication paths 306 illustrate optional information transmissions in which information from a plurality of different electronic mail systems is concentrated at a single interface switch 304. The dotted line communication paths 307 illustrate connections to additional gateway switches with mailboxes 14 within electronic mail systems 1-N.

The function of the interface switches 304 is twofold. *Function* In the first place, the interface switches 304 ~~functions~~ as a security check to determine that information transmissions originating from a gateway switch with mailbox 14 represent transmissions which should be coupled to a hub switch 116 of the RF information transmission network 302. The security check is performed by the interface switch 304 comparing the identification number of the RF receiver 119 which has been added by either an

48

originating processor A-N or a gateway switch with
mailboxes 14 with permissible identification numbers or
the interface switch performing the addition of the
identification number. The interface switch 304 also
5 removes information added by the electronic mail
system 1-N to the information originated by the
originating processor A-N from the stored information
received from one of the gateway switches 14 and adds
information used by the RF information transmission
10 network 302 during transmission of the information
originated at the originating processor to a RF
receiver 119 in the RF information transmission
network 302 which receives the information and *transfer*
it to the destination processor A-N. Additionally, the
15 interface switch 304 encodes data, which is required to
format the display of the CRT of the destination
processor for the electronic mail system to which the
destination processor is connected, in the form of a
character or characters which are decoded by either the
20 RF receiver 119 or the destination processor A-N and
added in decoded form back to the information which is
processed by the destination processor with a format of
the electronic mail system to which the destination
processor A-N is connected.

25 The interface switches 304 function to store
information which has been stored by at least one
gateway switch 114 that is received from a plurality of
originating processors, assemble the information from a
plurality of originating processors into a packet
30 preferably having the format of that described above
with reference to the prior art in Fig. 6 and transmit
the packet to the hub switch 116 within the RF
information transmission network 302. While the
invention is not limited to the transmission of the
packets from the interface switch 304 to the hub

switch 116 of the RF information transmission system 302, the hub switch is the preferable node in the RF information transmission network to which communications from the gateway switches 14 should be transmitted as a consequence of it having jurisdiction over both lata switches 114 and the local switches 112 in the RF information transmission network which results in lesser network overhead.

The hub switch 116 receives the packet from the receiving interface switch 304 and disassembles the packet into information from the plurality of originating processors either within a single electronic mail system such as system 1 or from a plurality of electronic mail systems, such as systems 1-N, or from outside of any electronic mail system from at least one additional processor 312 which is connected directly to interface switch 304 to originate information to be transmitted to a destination processor A-N in an electronic mail system as described below. The RF information transmission network 302 transmits the disassembled information from the hub switch 116 including the identification number of the RF receiver ^{transferring} ~~relaying~~ information to the destination processor A-N to a local switch 112 storing the file 154 identified by the identification number and any destination 178 of the RF receiver in the RF information transmission network to which the information and identification number is to be transmitted by the RF information transmission network and adds any destination of the RF receiver to the information in accordance with the prior art system described above with reference to Figs. 2-6. The RF information transmission network in response to any added destination transmits the information and identification number to the destination in accordance

50

9 with the prior art system described above with reference to Figs. 2-6 for RF broadcast to the RF receiver 119 for ~~relaying~~ ^{transfer} to the destination processor A-N.

5 The information is transmitted to a receiving interface switch 304 from one or more gateway switches 14 by one or more electronic mail systems 1-N in response to an address of the receiving interface switch which has been added to the information
10 originated by the originating processor by either the originating processor or gateway switch. The information is transmitted from the receiving interface switch 304 to the RF information transmission network with an address of the destination processor, such as a
15 name of a user of the destination processor A-N, to receive the information which has been added by either the originating processor A-N, a gateway switch 14 or the receiving interface switch 304.

20 Various options exist for the adding of the address of the receiving interface switch and the address of the destination processor. Preferably, the address of the receiving interface switch is a code word, such as "TF-MOBOX", which is recognized throughout the electronic mail system when appended to
25 information as directing the information to be transmitted to the interface switch 304. The address of the destination processor is preferably the identification number of the RF receiver 119 within the RF information transmission network 302. The address
30 of the receiving interface switch may be added to the information originated by the originating processor, by a gateway switch 14 or by the originating processor A-N. The address of the receiving interface switch 304 may be added to the information by matching an
35 identification of the destination processor A-N which

57

may be the name of the individual utilizing the processor or some other information and adds an address of an interface switch such as the aforementioned "TF-MOBOX" stored with the matched identification of the destination processor to the information as the address of the receiving interface switch. Alternatively, the originating processor may be used to add the address of the receiving interface switch 14 by an inputting of the address of the receiving interface switch (TF-MOBOX) along with an identification of the destination processor A-N (name of recipient using the processor). The originating processor A-N may also add the address of the receiving interface switch 304 by matching an identification of the destination processor (name of the user of the processor) with a stored identification of a destination processor and adding an address of the interface switch (TF-MOBOX) stored with the matched identification of the destination processor to the information as the address of the receiving interface switch. The identification number may be added to the information originated by the originating processor or, alternatively, ^{may be} ~~is~~ added by the originating processor by matching an identification of the destination processor (the name of the user of the processor) with a stored identification of a destination processor (the authorized user of the destination processor) and adding an identification number stored with the matched identification of the destination processor to the information as the identification number of the RF receiver 119. Alternatively, the aforementioned matching process may be performed by either the gateway switch 14 or the interface switch 304.

The at least one additional processor 312 originates information from outside of any electronic

52

a 5 mail system. The processors 312 provide an address of
 at least one destination processor in an electronic
 mail system, such as the name of the user, to receive
 information transmitted by the RF information
 transmission system 302 or an identification number of
 the RF receiver 119 receiving information and relaying
 the information to the destination processor. The
 interface switch 304 which receives the information
 from each processor 312 adds information used by the RF
 10 information transmission network 302 during
 transmission of the information to the RF receiver 119
 receiving the information in the same manner as
 described above with respect to the interface
 switch 304.

15 The advantage of connecting the processors 312
 directly to the interface switch 304 is that the
 processors 312 are only required to have a telephone
 modem and support programming to format information for
 RF transmission to a destination processor A-N within
 20 any one of one or more electronic mail systems 1-N.
 The processors 312 are not required to have the
 necessary electronic mail system software present in
 originating processors A-N or interconnections with an
 electronic mail system. As a result of the connection
 25 to the interface switch 304, information originating
 from the additional processors 312 may be transmitted
 by RF transmission to a destination processor A-N
 within any one or a plurality of electronic mail
 systems with the user of the processor 312 or the
 30 processor 312 or the interface switch 304 only having
 to supply an identification number of the receiver 119
 to input information into the RF information
 transmission system 302 for RF transmission to a
 destination processor.

53

The difference between originating information by one of the additional processors 312 outside of any electronic mail system and originating information by one of the processors within one of the electronic mail systems is that the direct connection of the additional processor to the interface switch 304 eliminates the requirement for the adding of an address of the interface switch 304 which is required by the electronic mail systems to forward the information to the interface switch where necessary formatting of the information to be compatible with the RF information transmission system is performed. The interface switch 304 packetizes information originating from the additional processors 312 in the same manner as described above with respect to information originating from within an electronic mail system. Information from within an electronic mail system and originating from additional processors 312 outside of the electronic mail system may be formatted into the same packets which are forwarded to the hub switch 116. Additionally, an interface switch 304 may be connected only to the additional processors 312 to provide an interface only for processors outside of any electronic mail system to destination processors A-N within one or more electronic mail systems 1-N. The only information which is necessary to be inputted by the additional processors 312 is the address of the destination processor (user of the processor). The addition of the identification number of the receiver 119 may be added by matching of an identification of the destination processor with stored destination processors within the additional processor 312 or the interface switch 304 with an identification number of the receiver 119 ~~being~~ stored with an identification of a destination

9

54

processor A-N ~~being~~ used as an identification of the destination processor upon a match having been made.

Fig. 11 summarizes electronic mail message entry methods for messages (information) originating from
5 originating processors within an electronic mail system. The first entry method adds the address of the interface switch 304 and the destination processor preferably in the form of a user's name; the gateway switch 14 takes no action; and the interface switch 304
10 adds the identification number of the RF receiver 119. The second entry method adds the address of the interface switch 304 and the identification number of the receiver 119; the gateway switch 14 takes no action; and the interface switch 304 performs only the
15 function of verifying that the identification number which was added by the originating processor is a valid identification number within the RF information transmission network 302. In the third method, the originating processor adds the destination processor preferably in the form of the user's name; the gateway
20 switch adds the destination of the interface switch 304; and the interface switch 304 adds the identification of the receiver 119. In the fourth method, the originating processor adds the destination processor preferably in the form of the user's name
25 only; the gateway switch 14 adds an address of the interface switch 304 and the identification number of the receiver 119; and the interface switch takes no action other than verification that the identification
30 number of the receiver 119 added by the gateway switch 14 is valid. In the fifth method, the operator of the originating processor adds the destination processor, points to an icon displayed on a CRT associated with the originating processor and the
35 originating processor adds the address of the interface

55

switch 304; the gateway switch 14 adds the identification number of the receiver 119 and the interface switch 304 takes no action other than verification. In the sixth method, the operator of the
 5 originating processor adds the destination processor, the user of the originating processor points to an icon displayed by a CRT associated with the originating processor which causes the addition of the address of the interface switch 304; the gateway switch takes no
 10 action and the interface switch 304 adds the identification of the receiver 119. In the seventh method, the operator of the originating processor adds the destination processor, the user points to an icon displayed on a CRT associated with the originating
 15 processor causing the addition of the address of the interface switch 304 and the receiver identification number by comparing an identification of the destination processor, such as user name of the destination processor, to an identification of
 20 destination processors with identification numbers or RF receivers 119 which transfer information to the destination processor; the gateway switch 14 takes no action; and the interface switch 304 takes no action.

Fig. 12 illustrates a block diagram of an
 25 interface switch 304 in accordance with the present invention. The interface switch 304 has a main CPU 400 to which is connected a floppy drive 402 and a hard drive 404 for providing memory storage for use by the CPU in executing the various functions of the interface
 30 switch as described above. The program on pages 10-14 of the Appendix implements the function of the interface switch 304 in a 3B2 computer which interfaces with the Telefind Corporation data transmission network described in the above-referenced patents and the
 35 AT&T Corporation electronic mail system. A diagnostic

56

and maintenance port 406 is connected to the CPU in accordance with standard practice. A main bus 408 is coupled to a plurality of serial ports 410 which are connected in series with a multispeed modem 412 which is connected to one of the additional processors 312 as discussed above with reference to Fig. 9, to at least one gateway switch with mailboxes 14 in at least one electronic mail system and to a plurality of network ports which are connected to a plurality of X.25 modems 414 which are connected in series with a network port 416 which is connected to hub switch 116 of Fig. 9. A module bay controller 418 controls the bus 408 in accordance with standard practice. Alternatively, if the interface switch is not connected to a gateway switch with mailboxes 14, the interface switch functions only as a general purpose collector switch for the additional processors 312.

While the invention has been described in terms of its preferred embodiments, it should be understood that numerous modifications may be made thereto without departing from the spirit and scope as defined in the appended claims. For example, while the invention has been described in terms of utilizing a preferred RF information transmission network, it should be understood that the invention is equally applicable to other forms of RF transmission systems for broadcasting information originating from an originating processor within an electronic mail system or from an additional processor outside of any electronic mail system to a destination processor connected to an electronic mail system. It is intended that all such modifications fall within the scope of the appended claims.

57

Claims

1. An electronic mail system for transmitting information from one of a plurality of originating processors to at least one of a plurality of destination processors during operation comprising:

5 at least one gateway switch, a gateway switch storing information received from one of the at least one originating processor prior to transmission of the information to the at least one destination processor;

10 a RF information transmission network for transmitting stored information received from one of the at least one gateway switch by RF transmission to at least one destination processor;

15 at least one interface switch, an interface switch connecting a gateway switch to the RF transmission network and transmitting stored information received from one of the at least one gateway switch to the RF information transmission network; and wherein

20 the information is transmitted to a receiving interface switch by the electronic mail system in response to an address of the receiving interface switch which has been added to the information originated by the originating processor by either the
25 originating processor or gateway switch and the information is transmitted from the receiving interface switch to the RF information transmission network with an address of the destination processor to receive the
30 information which has been added by either the originating processor, a gateway switch or the receiving interface switch.

2. An electronic mail system in accordance with claim 1 wherein:

the receiving interface switch removes information added by the electronic mail system to the information originated by the originating processor from the stored information received from one of the at least one gateway switch and adds information used by the RF information transmission network during transmission of the information to the information originated by the originating processor to a RF receiver in the RF information transmission network which receives the information and relays it to the destination processor.

3. An electronic mail system in accordance with claim 1 wherein:

the address of the destination processor is an identification number of a RF receiver in the RF information transmission network which receives the information and relays it to the destination processor; and

the receiving interface switch stores information which has been stored by at least one gateway switch that is received from a plurality of originating processors, assembles the information from a plurality of originating processors into a packet and transmits the packet to the RF information transmission network.

4. An electronic mail system in accordance with claim 3 wherein the RF information transmission network comprises:

5 a switch which receives the packet from the receiving interface switch and disassembles the packet into information from the plurality of originating processors; and wherein

10 the RF information transmission network transmits the disassembled information, including the identification number of the RF receiver relaying information to a destination processor to a switch in the RF information transmission network storing a file identified by the identification number and any destination of the RF receiver in the RF information transmission network to which the information and identification number is to be transmitted by the RF information transmission network and adds any destination of the RF receiver to the information and the RF information transmission network in response to any added destination transmits the information and identification number to the destination for RF broadcast to the RF receiver for relaying to the destination processor.

25 5. An electronic mail system in accordance with claim 2 wherein:

the address of the destination processor is an identification number of a RF receiver in the RF transmission network which receives the information and relays it to the destination processor; and

30 the receiving interface switch stores information which has been stored by at least one gateway switch that is received from a plurality of originating processors, assembles the information from a plurality of originating processors into a packet and

transmits the packet to the RF information transmission network.

5 6. An electronic mail system in accordance with claim 5 wherein the RF information transmission network comprises:

10 a switch which receives the packet from the receiving interface switch and disassembles the packet into information from the plurality of originating processors; and wherein

15 the RF information transmission network transmits the disassembled information, including the identification number of the RF receiver relaying information to destination processor to a switch in the RF information transmission network storing a file identified by the identification number and any destination of the RF receiver in the RF information transmission network to which the information and identification number is to be transmitted by the
20 RF information transmission network and adds any destination of the RF receiver to the information and the RF information transmission network in response to any added destination transmits the information and identification number to the destination for
25 RF broadcast to the RF receiver for relaying to the destination processor.

7. An electronic mail system in accordance with claim 1 wherein:

30 the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a

different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

8. An electronic mail system in accordance with claim 2 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

9. An electronic mail system in accordance with claim 3 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

10. An electronic mail system in accordance with claim 4 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

11. An electronic mail system in accordance with claim 5 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

12. An electronic mail system in accordance with claim 6 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

13. An electronic mail system in accordance with claim 1 further comprising:

a RF receiver connectable to the destination processor and in response to connection of the RF receiver to the destination processor the RF receiver transfers information stored in a memory of the RF receiver received from the originating processor to the destination processor;

a number of originating processors is greater than a number of interface switches; and

a plurality of originating processors also function as destination processors with a RF receiver connected thereto.

14. An electronic mail system in accordance with claim 1 wherein:

the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

15. An electronic mail system in accordance with claim 1 wherein:

the address of the receiving interface switch is added by the originating processor.

5 16. An electronic mail system in accordance with claim 1 wherein:

10 the address of the destination processor is an identification number of a RF receiver receiving the information and relaying the information to the destination processor and is added to the information originated by the originating processor by the originating processor.

17. An electronic mail system in accordance with claim 1 wherein:

15 the address of the destination processor is an identification number of a RF receiver receiving the information and relaying the information to the destination processor and is added to the information originated by the originating processor by the gateway switch.
20

18. An electronic mail system in accordance with claim 1 wherein:

25 the address of the destination processor is an identification number of a RF receiver receiving the information and relaying the information to the destination processor and is added to the information originated by the originating processor by the receiving interface switch.

19. An electronic mail system in accordance with claim 2 wherein:

the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

20. An electronic mail system in accordance with claim 2 wherein:

the address of the receiving interface switch is added by the originating processor.

21. An electronic mail system in accordance with claim 2 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the originating processor.

22. An electronic mail system in accordance with claim 2 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the gateway switch.

23. An electronic mail system in accordance with claim 2 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the receiving interface switch.

24. An electronic mail system in accordance with claim 3 wherein:

the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

25. An electronic mail system in accordance with claim 13 wherein:

the address of the receiving interface switch is added by the originating processor.

5 26. An electronic mail system in accordance with claim 13 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the originating processor.

10 27. An electronic mail system in accordance with claim 13 wherein:

a the identification number of the RF receiver is added to the information originated by the originating processor by the gateway switch.

15 28. An electronic mail system in accordance with claim 13 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the receiving interface switch.

20

29. An electronic mail system in accordance with claim 4 wherein:

the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

25

30. An electronic mail system in accordance with claim 4 wherein:

the address of the receiving interface switch is added by the originating processor.

31. An electronic mail system in accordance with claim 4 wherein:

5 the identification number of the RF receiver receiving the information and relaying the information to the destination processor and is added to the information originated by the originating processor by the originating processor.

32. An electronic mail system in accordance with claim 4 wherein:

10 the identification number of the RF receiver is added to the information originated by the originating processor by the gateway switch.

33. An electronic mail system in accordance with claim 4 wherein:

15 the identification number of the RF receiver is added to the information originated by the originating processor by the receiving interface switch.

34. An electronic mail system in accordance with claim 5 wherein:

20 the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

35. An electronic mail system in accordance with claim 5 wherein:

25 the address of the receiving interface switch is added by the originating processor.

36. An electronic mail system in accordance with claim 5 wherein:

5 the identification number of the RF receiver is added to the information originated by the originating processor by the originating processor.

37. An electronic mail system in accordance with claim 5 wherein:

10 the identification number of an RF receiver is added to the information originated by the originating processor by the gateway switch.

38. An electronic mail system in accordance with claim 5 wherein:

15 the identification number of the RF receiver is added to the information originated by the originating processor by the receiving interface switch.

39. An electronic mail system in accordance with claim 6 wherein:

20 the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

40. An electronic mail system in accordance with claim 6 wherein:

25 the address of the receiving interface switch is added by the originating processor.

41. An electronic mail system in accordance with claim 6 wherein:

30 the identification number of the RF receiver is added to the information originated by the originating processor by the originating processor.

42. An electronic mail system in accordance with claim 6 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the gateway switch.

43. An electronic mail system in accordance with claim 6 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the receiving interface switch.

44. An electronic mail system in accordance with claim 14 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

45. An electronic mail system in accordance with claim 15 wherein:

the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

46. An electronic mail system in accordance with claim 15 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

47. An electronic mail system in accordance with claim 16 wherein:

the identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

48. An electronic mail system in accordance with claim 16 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

49. An electronic mail system in accordance with claim 17 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

50. An electronic mail system in accordance with claim 18 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

51. An electronic mail system in accordance with claim 19 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

52. An electronic mail system in accordance with claim 20 wherein:

the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

53. An electronic mail system in accordance with claim 20 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

54. An electronic mail system in accordance with claim 21 wherein:

an identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

55. An electronic mail system in accordance with claim 21 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

56. An electronic mail system in accordance with claim 22 wherein:

5 the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

10 57. An electronic mail system in accordance with claim 23 wherein:

15 the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

20 58. An electronic mail system in accordance with claim 24 wherein:

25 the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

59. An electronic mail system in accordance with claim 25 wherein:

the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

60. An electronic mail system in accordance with claim 25 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

61. An electronic mail system in accordance with claim 26 wherein:

an identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

62. An electronic mail system in accordance with claim 26 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

63. An electronic mail system in accordance with claim 27 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

64. An electronic mail system in accordance with claim 28 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

65. An electronic mail system in accordance with claim 29 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

66. An electronic mail system in accordance with claim 30 wherein:

5 the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

67. An electronic mail system in accordance with claim 30 wherein:

10 the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the
15 address of the receiving interface switch.

68. An electronic mail system in accordance with claim 31 wherein:

20 an identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

69. An electronic mail system in accordance with claim 31 wherein:

25 the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to
30 the information as the identification number.

70. An electronic mail system in accordance with claim 32 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

71. An electronic mail system in accordance with claim 33 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

72. An electronic mail system in accordance with claim 34 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

73. An electronic mail system in accordance with claim 35 wherein:

the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

74. An electronic mail system in accordance with claim 35 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

75. An electronic mail system in accordance with claim 36 wherein:

an identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

76. An electronic mail system in accordance with claim 36 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

77. An electronic mail system in accordance with claim 37 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

78. An electronic mail system in accordance with claim 38 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

79. An electronic mail system in accordance with claim 39 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

80. An electronic mail system in accordance with claim 40 wherein:

the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

81. An electronic mail system in accordance with claim 40 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

82. An electronic mail system in accordance with claim 41 wherein:

an identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

83. An electronic mail system in accordance with claim 41 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

84. An electronic mail system in accordance with claim 42 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

85. An electronic mail system in accordance with claim 43 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

Add
B₁

ADDC3

Add D₁ >

Add E₁ >

Add F₁ >

Appendix

An Appendix containing a listing of control programs for controlling the transmission of information between an RF receiver and a destination processor and controlling the operation of an interface switch in accordance with the invention is attached. The programs are written in the C programming language. The program for controlling the transmission of information from the RF receiver to the destination processor appears at pages 1-9 and the program for controlling the operation of the interface switch appears at pages ¹⁰⁻¹²~~10-14~~. The Appendix contains subject matter which is copyrighted. A limited license is granted to anyone who requires a copy of the program disclosed therein for purposes of understanding or analyzing the invention, but no license is granted to make a copy for any other purposes including the loading of a processing device with code in any form or language.

9
10
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

Cross-Reference to Related Applications

Reference is made to other applications which are filed on even date herewith which are incorporated by reference in their entirety.

5

United States Patent Application Serial No. 07,702,319 (now US Patent 5,438,611), entitled "Electronic Mail System With RF Communications to Mobile Processors Originating From Outside of the Electronic Mail System" ~~(Attorney Docket No. 780-29766X00);~~ and

10

United States Patent Application Serial No. 07,702,938 (now US Patent 5,479,472), entitled "System for Interconnecting Electronic Mail Systems By RF Communications" ~~(Attorney Docket No. 780-29767X00);~~

3



780.29643CX1

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Prior Application Serial No.: 07/702,939

Filed: May 20, 1991

Examiner: G. Oehling

Group: 2608

Honorable Commissioner of
Patents and Trademarks
Washington, D. C. 20231

Sir:

This is a request for filing a Continuation application under 37 C.F.R. §1.60 of pending application Serial No. 07/702,939, filed May 20, 1991, entitled "ELECTRONIC MAIL SYSTEM WITH RF COMMUNICATIONS TO MOBILE PROCESSORS", by Thomas J. Campana, Jr., Michael P. Ponschke and Gary F. Thelen.

[XX] 1. Enclosed is a copy of the prior application as originally filed and an affidavit or declaration verifying it as a true copy.

[XX] 2. The filing fee is calculated below:

CLAIMS AS FILED, LESS ANY CLAIMS CANCELLED BY AMENDMENT

<u>For</u>	<u>Number Filed</u>		<u>Number Extra</u>		<u>Rate</u>	<u>Basic Fee \$365.00</u>
Total Claims:	55	-20 =	35	x	\$11.00 =	\$385.00
Ind. Claims:	2	-3 =	0	x	\$ 0.00 =	0.00
[] Multiple Dependent Claims				x	\$ =	0.00
Attached hereto is a check in the amount of						\$750.00

- [XX] 3. To the extent necessary, Applicants petition for an extension of time under 37 CFR §1.136 in Serial No. 07/702,939, filed May 20, 1991. Please charge any shortage in fees, or credit any overpayment thereof, to Deposit Account No. 01-2135 (780.29643CX1). A duplicate copy of this sheet is attached.
- [XX] 4. Cancel original claims 2-85 of the prior application before calculating the filing fee.
- [XX] 5. Amend the specification by inserting the following before the first line thereof:
- This application is a Continuation Application of U.S. Serial Nos. 07/702,939, filed May 20, 1991; 07/702,938, filed May 20, 1991 and 08/247,466, filed May 23, 1994; which is a Continuation of U.S. Serial No. 07/702,319, filed May 20, 1991 (now abandoned).--
- [XX] 6. New formal drawings are enclosed.
- [XX] 7. Informal drawings are enclosed.
- [XX] 8. The prior application is assigned of record to:
- NTP Incorporated
Annandale, Virginia
- A copy of the recorded Assignment is also enclosed.
- [XX] 9. The power of attorney in the prior application is to:
- Antonelli, Terry, Stout & Kraus
Suite 600
1919 Pennsylvania Avenue, N.W.
Washington, D.C. 20006
- [XX] 10. The power appears in the original papers in the prior application. A copy of the Power and the Supplemental Declaration filed in the parent case are also enclosed.
- [XX] 11. A Change of Address is also being submitted concurrently herewith.
- [XX] 12. A copy of the Small Entity Declaration filed in the parent application is also enclosed.

- [XX] 13. Address all future communications in connection with this application to:


ANTONELLI, TERRY, STOUT & KRAUS
Suite 1800
1300 North Seventeenth Street
Arlington, Virginia 22209

- [XX] 14. A Preliminary Amendment is enclosed. (Any claims added by the Preliminary Amendment have been properly numbered consecutively beginning with the number next following the highest numbered original claim in the prior application.)
- [XX] 15. I hereby verify that the attached papers are a true copy of prior application Serial No. 07/702,393 as originally filed in the U.S. Patent and Trademark office on May 20, 1991.

The undersigned declares further that all statements made herein of his own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Respectfully submitted,

ANTONELLI, TERRY, STOUT & KRAUS


Donald E. Stout
Registration No. 26,422
(703) 312-6600

Date: May 18, 1995

Enclosures

DES:dlh

Copyright Thomas Campana, Jr. 1991

define ATT_MAIL_FILE
define DELIMITER

"PHONECALL"
"End of Telefind Network Message"


```

#include <string.h>
#include <time.h>
#include <stdio.h>
#include <dos.h>
#include "safari.h"

void main(void)
{
    FILE *infile,*outfile;
    char buffer[81],chr,timestr[6],datestr[9];
    char msg_run[6];
    int msg_run_opt = 0;
    char *ptr;
    int x,day,month,lines1,attmail=0;
    time_t t;

    if ((infile = fopen(ATT_EMAIL_FILE,"rt")) == NULL)
    {
        printf("%s does not exist\n",ATT_EMAIL_FILE);
        exit(0);
    }
    if ((outfile = fopen("inbox.BES","wt")) == NULL)
    {
        printf("Can't open (INBOX.BES)\n");
        exit(0);
    }

    for(;;)
    {
        /* get characters from .bcp file */
        x = 0;
        do
        {
            chr = fgetc(infile);
            if (feof(infile))
            {
                fclose(infile);
                fclose(outfile);
                exit(0);
            }
            buffer[x++] = chr;
        }
        /* until end of line */
        while (chr != '\n' && x != 80);

        buffer[x] = '\0'; /* terminate it */

        if ((line = 1)
        {
            ptr = strchr(buffer,':');
            if (ptr-buffer == 2) /* use 3rd character */
            {
                sscanf(buffer,"%i",&msg_run);
                msg_run_opt = 1;
                ptr++;
            }
            else
                ptr = buffer;

            if (*ptr == ':' && *(ptr+1) == '0')
                attmail = 1;
        }

        if (attmail)
        {
            switch(line)

```

```

    case 1:
        /* datestr = mm/dd, timestr = hh:mm */
        ascanf(datestr, "%d/%d", &month, &day);
        /* get year from pc */

        t = time(NULL);
        fprintf(outfile, "Date: %s", ctime(&t));
        break;

    case 2:
        fprintf(outfile, "From: %s", buffer);
        break;

    case 3:
        fprintf(outfile, "Subject: %s", buffer);
        fprintf(outfile, "To: <name here>\n");
        if (msg_run_opt)
            fprintf(outfile, "Message %d\n", msg_run);
        break;

    default:
        fprintf(outfile, "%s", buffer);
        break;
    }
}
else
{
    if ((line == 1)
    {
        t = time(NULL);
        fprintf(outfile, "Date: %s", ctime(&t));
        fprintf(outfile, "From: timestr\n");
        fprintf(outfile, "Subject: Telefind Network Message\n");
        fprintf(outfile, "To: <name here>\n");
        if (msg_run_opt)
        {
            fprintf(outfile, "Message %d\n", msg_run);
            fprintf(outfile, "%s", buffer+3);
        }
        else
            fprintf(outfile, "%s", buffer);
    }
    else
        fprintf(outfile, "%s", buffer);
}

if (strcmp(buffer, DELIMITER) == 0)
{
    msg_run_opt = line = attach = 0;
}

line++;
}

```

```

Author:      MICHAEL P. PORROCKE, SR.
              05/13/91

Program:     BAPARIS.C
Purpose:     TO EXTRACT MESSAGES FROM A TELEFONO PAGER
              VIA RS-232 PORT ON A PC

Compiler:    TURBO C++ 1.0
Memory Model: SMALL

```

```

*/

#include <dos.h>
#include <stdio.h>
#include <conio.h>
#include <string.h>
#include <stdlib.h>
#include "safari.h"

/*  CONSTANTS  */

#define DTR_HI      0x01
#define OTE_LO      0x1e
#define RTS_HI      0x02
#define RTS_LO      0x1d
#define DSR_HI      0x20
#define RING_IN     0x40
#define CD_HI       0x80
#define FIVE_TICK   5
#define FIVE_SEC     96
#define TWELVE_SEC   220
#define LOG_FILE     "LOG"
#define INTRO_STRING "Please standby, retrieving messages ..."

/*  FUNCTION PROTOTYPES  */

int beep(void);
void busyoff(void);
void busyon(void);
void dloff(void);
void dlon(void);
int link(void);
void print_message(void);
int rxdone(void);
int strobe(void);
int strobe_data(void);
unsigned ticks(void);
int timeout(unsigned start, int delay);

/*  VARIABLE DECLARATIONS  */

char pager_buffer[31];
int com_base, control_reg, status_reg, log_flag;
FILE *log_file;

void main(int num_arg, char **args)
{
    unsigned start;
    int restart, i;

    com_base = 0x3f8; /* use com 1 unless command line denotes otherwise */

    /* get command line arguments */
}

```

/* all command line arguments begin with a single '-' and must be separated by a single space between each other and the program name

```
-1    Use CCK port 1
-2    Use CCK port 2
-p    Log all activity to a file named LOG */
```

```
if (num_arg > 1)
{
    for (x=1; x<num_arg; x++)
    {
        if (strcmp(optarg, "-1") == 0)
            com_base = 0x3f8;
        if (strcmp(optarg, "-2") == 0)
            com_base = 0x2f8;
        if (strcmp(optarg, "-p") == 0)
            log_flag = 1;
    }
}

if (log_flag)
{
    if ((log_file = fopen(LOG_FILE, "w")) == NULL)
        printf("Unable to open LOG file\n");

    control_reg = com_base + 4;
    status_reg = com_base + 6;

    clrscr();

    if ((link()) == 0) /* is pager attached ? */
    {
        printf("Please attach Message Receiver \n");
        exit(0);
    }

    busyon(); /* start busy at logic high */

    if (log_flag)
        fprintf(log_file, "Initiating process \n");
    printf("Start\n", INT8_STRING);
    delay(); /* push display button */
    sleep(2);
    do
    {
        start = ticks();
        restart = 0;
        do
        {
            if (beep())
            {
                print_message();
                restart = 1;
                start += TWELVE_DEC;
                break;
            }
        }
        /* hold display button for 12 seconds */
        while(1 timeout(start, TWELVE_DEC));
    }
    while(restart);

    delay(); /* release the display button */
    if (log_flag)
    {
        fprintf(log_file, "Process Complete \n");
    }
}
```

```

        fclose(log_file);
    }

    /*          paper beep          */
    int beep(void)
    {
        /*          accesses the BI line via the Status Register
           which is activated when the paper beeps          */

        unsigned start;

        start = ticks();
        while ( ! timeout(start,FIVE_TICK))
        {
            if ((inportb(status_reg) & BING_IE) == 0 )
                return(1);
        }
        return(0);
    }

    /*          busyon & busyoff toggle the DTB line via the
           Control Register to strobe in data from the paper          */

    void busyoff(void)
    {
        outportb(control_reg,inportb(control_reg) | DTB_HI);
    }

    void busyon(void)
    {
        outportb(control_reg,inportb(control_reg) & DTB_LO);
    }

    /*          dison & disoff toggle the RTS line via the Control Register
           to simulate the pressing of the display button on the paper          */

    void dison(void)
    {
        outportb(control_reg,inportb(control_reg) | RTS_HI);
    }

    void disoff(void)
    {
        outportb(control_reg,inportb(control_reg) & RTS_LO);
    }

    int link(void)
    {
        /*          accesses the CD line via the Status Register
           which is logic high when paper is connected          */

        if ((inportb(status_reg) & CD_HI) == 0)
            return(0);
        return(1);
    }

    void print_message(void)
    {
        FILE *ffile;
        unsigned start;
        int x,y=0,z=0,chr,bit;
    }

```

```

busyoff(); /* ready to accept paper data */

/* read until end code received */
while (chr != 3)
(
    chr = 0;
    start = ticks();

    /* wait for start bit */

    do
    (
        bit = strobe();
        if (bit == 0)
            break;
    )
    while (itimerout(start, FIVE_SEC));

    if (bit)
    (
        if (log_flag)
            fprintf(log_file, "Transmission Error, recheck connection\n");
        dieoff();
        exit(0);
    )

    /* strobe out 8 bit data */

    for (x=1; x<9; x++)
    (
        chr <<= 1;
        chr |= bit = strobe_data();
    )

    /* clear out stop bits */
    for (x=1; x<3; x++)
    (
        strobe_data();
    )

    /* extract start and end codes from message

    paper signon      C2, 18, 00, 33
    paper signoff     03 */

    if ((y > 3) && (chr != 3))
    (
        /* paper characters 96 and 97 are converted to
        0x9A and 0x9B to display on paper */

        if (chr == 0x9A) /* convert to C2 */
            chr = '\n';
        if (chr == 0x9B) /* convert to TAB */
            chr = 0x09;

        paper_buffer[z] = chr;
        z++;
    )
    y++;
)

paper_buffer[z] = '\0'; /* null terminate */

busyon(); /* finished receiving data */

```

```

if (log_file)
    fprintf(log_file, "%s\n", pager_buffer);

if ((file = fopen(ATT_EMAIL_FILE, "at")) == NULL)
    fprintf(log_file, "Unable to open (FPCBOX.TMP)\n");
else
{
    fprintf(file, "%s\n", pager_buffer);
    fprintf(file, "%s", DELIMITER);
    fclose(file);
}

start = ticks();
while(!timeout(start, FIVE_SEC))
{
    /* wait for erase beep */
    if (beep()) break;
}
sleep(1); /* wait one more second */
}

int rdata(void)
{
    /* addresses the DSR line via the Status Register
    which returns the data value */
    if ((inportb(status_reg) & DSR_M1))
        return(0);
    return(1);
}

int strobe(void)
{
    int bit;

    busyon();
    delay(1);
    busyoff();
    delay(4);
    bit = rdata();
    return(bit);
}

int strobe_data(void)
{
    int bit;

    busyon();
    delay(2);
    bit = rdata();
    busyoff();
    delay(1);
    return(bit);
}

unsigned ticks(void)
{
    /* returns timer ticks (approx. 18.2/sec)
    using only lower registers */

    union REGS in, out;

    in.h.eax = 0x0;
    in.h.edi = 0x1;
    return(out.h.dh);
}

```

```

)
int timeout(unsigned start, int delay)
(
    /*      used for timing events of up to approx. 1 hour.
        used in conjunction w/ticks()      */

    unsigned current;

    current = ticks();
    if (start == current && (start + delay) < current)
        return(1);
    if (start > current && (start + 65535 + delay) < current)
        return(1);
    return(0);
)

```

(D

```

100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
2583
2584
2585
2586
2587
2588
2589
2590
2591
2592
2593
2594
2595
2596
2597
2598
2599
2600
2601
2602
2603
2604
2605
2606
2607
2608
2609
2610
2611
2612
2613
2614
2615
2616
2617
2618
2619
2620
2621
2622
2623
2624
2625
2626
2627
2628
2629
2630
2631
2632
2633
2634
2635
2636
2637
2638
2639
2640
2641
2642
2643
2644
2645
2646
2647
2648
2649
2650
2651
2652
2653
2654
2655
2656
2657
2658
2659
2660
2661
2662
2663
2664
2665
2666
2667
2668
2669
2670
2671
2672
2673
2674
2675
2676
2677
2678
2679
2680
2681
2682
2683
2684
2685
2686
2687
2688
2689
2690
2691
2692
2693
2694
2695
2696
2697
2698
2699
2700
2701
2702
2703
2704
2705
2706
2707
2708
2709
271
```



```

/* mark the end of the command line you built, so you can add ending
   delimiter */
sys_command[i] = NULL;
/* add the ending quote for the users message so snell wont
   interpret special characters */
strcat(sys_command, "\"");
/* execute command you built */
system(sys_command);

printf("sending message: %s\n", sys_command);

}
else (
    if(strlen(msg) == 0 ) {
        return(0);
    }
    /* print error for invalid message length */
    printf("telemail error: invalid message length: %s\n", msg);
    return(0);
}

return(1);
}

.....
.
. function: getline(hold-buffer, input-file-pointer)
. arguments: pointer to buffer where line read will be heald,
.             file pointer to input file
. description: reads 1 line of text from the input line and stores the
.             line read into the buffer passed.
. returns: -1 if EOF or number of characters read in
.
.....
getline(buff, fp)
char *buff;
FILE *fp;
{
    int ch, cnt;

    /* keep on reading charactrs from file so long as end of file not
       reached or char is the end of line */
    for(cnt = 0; ((ch = fgetc(fp)) != EOF) && ch != '\n'; cnt++) {
        /* MOD BY OT 11/29/90 convert tab to space */
        /* convert tabs to single space */
        if(ch == 9) {
            ch = ' ';
        }
        /* MOD BY OT 11/29/90 dont allow control char */
        /* only load in ascii characters */
        if(isprint(ch) != 0) {
            buff[cnt] = ch;
        }
        else {
            /* turn control characters to spaces */
            buff[cnt] = ' ';
        }
    }
    /* mark the end of the buffer you built */
    buff[cnt] = '\0';
}

```

```

.....
.
.   function: send_mesg(message-pointer)
.   arguments: pointer to text message(capcode,text) to be sent
.   description: takes passed message text makes sure the first 8 positions
.                 are numeric(capcode). it builds and executes the network
.                 send command(netsend.sh) to send the message passed.
.   returns: 0 if not sent otherwise the number of characters sent out
.
...../
int send_mesg(mesg)
char *mesg;
{
    char sys_command[700];
    int i;
    int ch;
    char *mesg_ptr;

    /* left justify the message passed to remove leading spaces */
    stripust(mesg, 512);
    /* trim off trailing blank spaces from the message */
    strtrim(mesg);

    /* make sure you have a capcode at least */
    if(strlen(mesg) > 8) {

        /* start to build the command to be executed to send message retrieved
           from the mail box */
        strcpy(sys_command, "netsend.sh ");

        /* loop while still more characters in the message */
        for(mesg_ptr = mesg, i = 11; *mesg_ptr != NULL; i++, mesg_ptr++) {

            /* make sure the first 8 positions of the message are numeric */
            if((i < 19) && (*mesg_ptr < '0' || *mesg_ptr > '9')) {
                printf("telemail error: invalid capcode: %s\n", mesg);
                return 0;
            }

            /* is the user didnt separete capcode & message then insert a
               space into the command */
            if(i == 19 && *mesg_ptr != ' ') {
                sys_command[19] = ' ';
                i = 20;
            }

            /* enclose the users message with ' so shell wont interpret
               special characters */
            if(i == 20) {
                sys_command[20] = '\'';
                i = 21;
            }

            /* put the character from the message onto to the
               command to be executed */
            sys_command[i] = *mesg_ptr;
        }
    }
}

```

```

/* since your just starting clear the message area */
memset(mesg, NULL, MAXMSGLEN);

/* keep on geting lines from the file until you reach end of file */
while(getline(buff, fp) != -1) {

    /* every mail message start with the word "From " */
    if(strncmp(buff, "From ", 5) == 0) {
        /* set flag telling you are currently going thru mail header
           so you dont add it to the message */
        in_header = 1;
        /* call routine to the last message if any exists */
        send_mesg(mesg);
        continue;
    }

    /* a mail header end with the following string */
    if(strncmp(buff, "Content-Length:", 15) == 0) {
        /* turn off flag so you know you are no longer in mail
           message header */
        in_header = 0;
        /* clear the old message since this is a new one */
        memset(mesg, NULL, MAXMSGLEN);
        continue;
    }

    /* if the line you are now reading in not part of the mail header
       add it to the message */
    if(in_header == 0) {
        strljust(buff, 512);
        strtrim(buff);
        /* make sure you dont add more than the message length */
        if( (strlen(buff) + strlen(mesg)) < MAXMSGLEN) {
            strcat(mesg, " ");
            strcat(mesg, buff);
        }
    }
}

/* enc of read line while */

/* send the last message in the file */
send_mesg(mesg);

```



APPENDIX

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

Illus#1-12/2

Copyright Thomas Campana, Jr. 1991

#define ATT_EMAIL_FILE
#define DELIMITER

"TFMOBOX.TMP"
"End of Telefind Network Message\n"

58

58

```

#include <string.h>
#include <time.h>
#include <stdio.h>
#include <dos.h>
#include "safari.h"

void main(void)
{
    FILE *infile,*outfile;
    char buffer[81],chr,timestr[6],datestr[9];
    char msg_num[4];
    int msg_num_opt = 0;
    char *ptr;
    int x,day,month,line=1,attmail=0;
    time_t t;

    if ((infile = fopen(ATT_EMAIL_FILE,"rt")) == NULL)
    {
        printf("%s does not exist\n",ATT_EMAIL_FILE);
        exit(0);
    }
    if ((outfile = fopen("tfmobox.$$$","wt")) == NULL)
    {
        printf("Can't open TFMBOX.$$$\n");
        exit(0);
    }

    for(;;)
    {
        /*      get characters from .tmp file      */
        x = 0;
        do
        {
            chr = fgetc(infile);
            if (feof(infile))
            {
                fclose(infile);
                fclose(outfile);
                exit(0);
            }
            buffer[x++] = chr;
        }
        /*      until end of line      */
        while (chr != '\n' && x != 80);

        buffer[x] = '\0';      /*      terminate it      */

        if (line == 1)
        {
            ptr = strchr(buffer,');');
            if (ptr-buffer == 2)      /*      was 3rd character      */
            {
                sscanf(buffer,"%[^)]",msg_num);
                msg_num_opt = 1;
                ptr++;
            }
            else
                ptr = buffer;

            if (*ptr == ':' && *(ptr+1) == '0')
                attmail = 1;
        }

        if (attmail)
        {
            switch(line)

```

```

(
    case 1:
        /*      datestr = mm/dd, timestr = hh:mm      */
        sscanf(datestr,"%d/%d",&month,&day);          */
        /*      get year from pc      */

        t = time(NULL);
        fprintf(outfile,"Date: %s",ctime(&t));
        break;
    case 2:
        fprintf(outfile,"From: %s",buffer);
        break;
    case 3:
        fprintf(outfile,"Subject: %s",buffer);
        fprintf(outfile,"To: <Name here>\n");
        if (msg_num_opt)
            fprintf(outfile,"Message #s\n",msg_num);
        break;
    default:
        fprintf(outfile,"%s",buffer);
        break;
}
else
(
    if (line == 1)
    (
        t = time(NULL);
        fprintf(outfile,"Date: %s",ctime(&t));
        fprintf(outfile,"From: tfmobox\n");
        fprintf(outfile,"Subject: Telefind Network Message\n");
        fprintf(outfile,"To: <Name here>\n");
        if (msg_num_opt)
        (
            fprintf(outfile,"Message #s\n",msg_num);
            fprintf(outfile,"%s",buffer+3);
        )
        else
            fprintf(outfile,"%s",buffer);
    )
    else
        fprintf(outfile,"%s",buffer);
)

if (strcmp(buffer,DELIMITER) == 0)
(
    msg_num_opt = line = attmail = 0;
)

line ++;
)

```

/*

Author: MICHAEL P. PONSCHKE, SR.
03/13/91

Program: SAFARI3.C
Purpose: TO EXTRACT MESSAGES FROM A TELEFIND PAGER
VIA IN RS-232 PORT ON A PC

Compiler: TURBO C++ 1.0
Memory Model: SMALL

*/

```
#include <dos.h>
#include <stdio.h>
#include <conio.h>
#include <string.h>
#include <stdlib.h>
#include "safari.h"
```

/* CONSTANTS */

```
#define DTR_HI                   0x01
#define DTR_LO                   0xfe
#define RTS_HI                   0x02
#define RTS_LO                   0xfd
#define DSR_HI                   0x20
#define RING_IN                  0x40
#define CD_HI                    0x80
#define FIVE_TICK                5
#define FIVE_SEC                  96
#define TWELVE_SEC               220
#define LOG_FILE                 "LOG"
#define INTRO_STRING             "Please standby, retrieving messages ..."
```

/* FUNCTION PROTOTYPES */

```
int beep(void);
void busyoff(void);
void busyon(void);
void disoff(void);
void dison(void);
int link(void);
void print_message(void);
int rxdata(void);
int strobe(void);
int strobe_data(void);
unsigned ticks(void);
int timeout(unsigned start, int delay);
```

/* VARIABLE DECLARATIONS */

```
char pager_buffer[511];
int com_base, control_reg, status_reg, log_flag;
FILE *log_file;
```

```
void main(int num_arg, char **args)
```

```
{
```

```
    unsigned start;
    int restart,x;
```

```
    com_base = 0x3f8;           /*   use com 1 unless command line denotes otherwise   */
```

```
    /*    get command line arguments                    */
```


* all command line arguments begin with a single '-' and must be separated by a single space between each other and the program name

```
-1      Use COM port 1
-2      Use COM port 2
-F      Log all activity to a file named LOG      */
```

```
if (num_arg > 1)
{
    for (x=1; x<num_arg; x++)
    {
        if (strcmp(args[x],"-1") == 0)
            com_base = 0x3f8;
        if (strcmp(args[x],"-2") == 0)
            com_base = 0x2f8;
        if (strcmp(args[x],"-F") == 0)
            log_flag = 1;
    }
}

if (log_flag)
    if ((log_file = fopen(LOG_FILE,"at")) == NULL)
        printf("Unable to open LOG\n");

control_reg = com_base + 4;
status_reg = com_base + 6;

clrscr();

if (link() == 0)      /* is pager attached ?      */
{
    printf("Please attach Message Receiver \n");
    exit(0);
}

busyon();      /* start busy at logic high      */

if (log_flag)
    fprintf(log_file,"Initiating process \n");
printf("%s\n",INTRO_STRING);
dison();      /* push display button      */
sleep(2);
do
{
    start = ticks();
    restart = 0;
    do
    {
        if (beep())
        {
            print_message();
            restart = 1;
            start -= TWELVE_SEC;
            break;
        }
    }
    /* hold display button for 12 seconds      */
    while(! timeout(start,TWELVE_SEC));
}
while(restart);

disoff();      /* release the display button      */
if (log_flag)
{
    fprintf(log_file,"Process Complete \n");
```

```

        fclose(log_file);
    }

}

/*          pager beep          */
int beep(void)
{
    /*      accesses the RI line via the Status Register
       which is activated when the pager beeps      */

    unsigned start;

    start = ticks();
    while ( ! timeout(start,FIVE_TICK))
    {
        if ((inportb(status_reg) & RING_IN) == 0 )
            return(1);
    }
    return(0);
}

/*      busyon & busyoff toggle the DTR line via the
Control Register to strobe in data from the pager      */
void busyoff(void)
{
    outportb(control_reg,inportb(control_reg) | DTR_HI);
}

void busyon(void)
{
    outportb(control_reg,inportb(control_reg) & DTR_LO);
}

/*      dison & disoff toggle the RTS line via the Control Register
to simulate the pressing of the display button on the pager      */
void dison(void)
{
    outportb(control_reg,inportb(control_reg) | RTS_HI);
}

void disoff(void)
{
    outportb(control_reg,inportb(control_reg) & RTS_LO);
}

int link(void)
{
    /*      accesses the CD line via the Status Register
       which is logic high when pager is connected      */

    if ((inportb(status_reg) & CD_HI) == 0)
        return(0);
    return(1);
}

void print_message(void)
{
    FILE *file;
    unsigned start;
    int x,y=0,z=0,chr,bit;

```

```

busyoff(); /* ready to accept pager data */

/* read until end code received */
while (chr != 3)
{
    chr = 0;
    start = ticks();

    /* wait for start bit */

    do
    {
        bit = strobe();
        if (bit == 0)
            break;
    }
    while (!timeout(start,FIVE_SEC));

    if (bit)
    {
        if (log_flag)
            fprintf(log_file,"Transmission Error, recheck connection\n");
        disoff();
        exit(0);
    }

    /* strobe out 8 bit data */

    for (x=1; x<9; x++)
    {
        chr <<= 1;
        chr += bit = strobe_data();
    }

    /* clear out stop bits */
    for (x=1;x<3;x++)
    {
        strobe_data();
    }

    /* extract start and end codes from message

    pager signon      02, 1B, 0D, 33
    pager signoff     03 */

    if ((y > 3) && (chr != 3))
    {
        /* pager characters 96 and 97 are converted to
        0xFA and 0xFB to display on pager */

        if (chr == 0xfa) /* convert to CR */
            chr = '\n';
        if (chr == 0xfb) /* convert to TAB */
            chr = 0x09;

        pager_buffer[z] = chr;
        z ++;
    }
    y ++;
}

pager_buffer[z] = '\0'; /* null terminate */

busyon(); /* finished receiving data */

```

```

if (log_flag)
    fprintf(log_file,"%s\n",pager_buffer);

if ((file = fopen(ATT_EMAIL_FILE, "at")) == NULL)
    fprintf(log_file,"Unable to open TFMBOX.TMP\n");
else
{
    fprintf(file,"%s\n",pager_buffer);
    fprintf(file,"%s",DELIMITER);
    fclose(file);
}

start = ticks();
while(!timeout(start,FIVE_SEC))
{
    /* wait for erase beep */
    if (beep()) break;
}
sleep(1); /* wait one more second */
}

int rxdata(void)
{
    /* accesses the DSR line via the Status Register
       which returns the bits value */
    if (inportb(status_reg) & DSR_HI)
        return(0);
    return(1);
}

int strobe(void)
{
    int bit;

    busyon();
    delay(1);
    busyoff();
    delay(4);
    bit = rxdata();
    return(bit);
}

int strobe_data(void)
{
    int bit;

    busyon();
    delay(2);
    bit = rxdata();
    busyoff();
    delay(1);
    return(bit);
}

unsigned ticks(void)
{
    /* returns timer ticks (approx. 18.2/sec)
       using only lower registers */

    union REGS in,out;

    in.x.ax = 0x0;
    int86(0x1a,&in,&out);
    return(out.x.dx);
}

```

```

t timeout(unsigned start, int delay)

```

```
/*      used for timing events of up to approx. 1 hour.
        used in conjunction w/ticks()      */
```

unsigned current;

```
current = ticks();
if (start <= current && (start + delay) < current)
    return(1);
if (start > current && (start - 65535 + delay) < current)
    return(1);
return(0);
```

[illegible]

```

/* mark the end of the command line you built,so you can add ending
   delimiter */
sys_command[i] = NULL;
/* add the ending quote for the users message so shell wont
   interepert special characters */
strcat(sys_command, "\\");
/* execute command you built */
system(sys_command);

printf("sending message: %s\n", sys_command);

}
else {
    if(strlen(mesg) == 0 ) {
        return(0);
    }
    /* print error for invalid message length */
    printf("telemail error: invalid message length: %s\n", mesg);
    return(0);
}

return(i);
}

/*****
*
* function: getline(hold-buffer, input-file-pointer)
* arguments: pointer to buffer where line read will be heald,
*            file pointer to input file
* description: reads 1 line of text from the input line and stores the
*            line read into the buffer passed.
* returns: -1 if EOF or number of characters read in
*
*****/
getline(buff, fp)
char *buff;
FILE *fp;
{
    int ch, cnt;

    /* keep on reading characetr from file so long as end of file not
       reached or char is the end of line */
    for(cnt = 0; ((ch = fgetc(fp)) != EOF) && ch != '\n'; cnt++) {
        /* MOD BY OT 11/29/90 convert tab to space */
        /* convert tabs to single space */
        if(ch == 9) {
            ch = ' ';
        }
        /* MOD BY OT 11/29/90 dont allow control char */
        /* only load in ascii characters */
        if(isprint(ch) != 0) {
            buff[cnt] = ch;
        }
        else {
            /* turn control characters to spaces */
            buff[cnt] = ' ';
        }
    }
    /* mark the end of the buffer you built */
    buff[cnt] = '\0';

```

```

/*****
*
*   function: send_mesg(message-pointer)
*   arguments: pointer to text message(capcode,text) to be sent
*   description: takes passed message text makes sure the first 8 positions
*                are numeric(capcode). it builds and executes the network
*                send command(netsend.sh) to sedn the message passed.
*   returns: 0 if not sent otherwise the number of characters sent out
*
*****/
int send_mesg(mesg)
char *mesg;
{
    char sys_command[700];
    int i;
    int ch;
    char *mesg_ptr;

    /* left justify the message passed to remove leading spaces */
    strljust(mesg, 512);
    /* trim off trailing blank spaces from the message */
    strtrim(mesg);

    /* make sure you have a capcode at least */
    if(strlen(mesg) > 8) {

        /* start to build the command to be executed to send message retrieved
           from the mail box */
        strcpy(sys_command, "netsend.sh ");

        /* loop while still more characters in the message */
        for(mesg_ptr = mesg, i = 11; *mesg_ptr != NULL; i++, mesg_ptr++) {

            /* make sure the first 8 positions of the message are numeric */
            if((i < 19) && (*mesg_ptr < '0' || *mesg_ptr > '9')) {
                printf("telemail error: invalid capcode: %s\n", mesg);
                return 0;
            }

            /* is the user didnt separete capcode & message then insert a
               space into the command */
            if(i == 19 && *mesg_ptr != ' ') {
                sys_command[19] = ' ';
                i = 20;
            }

            /* enclose the users message with ' so shell wont interpret
               special characters */
            if(i == 20) {
                sys_command[20] = '\'';
                i = 21;
            }

            /* put the character from the message onto to the
               command to be executed */
            sys_command[i] = *mesg_ptr;
        }
    }
}

```

```

/* since your just starting clear the message area */
memset(mesg, NULL, MAXMSGLEN);

/* keep on geting lines from the file until you reach end of file */
while(getline(buff, fp) != -1) {

    /* every mail message start with the word "From " */
    if(strncmp(buff, "From ", 5) == 0) {
        /* set flag telling you are currently going thru mail header
           so you dont add it to the message */
        in_header = 1;
        /* call routine to the last message if any exists */
        send_mesg(mesg);
        continue;
    }

    /* a mail header end with the following string */
    if(strncmp(buff, "Content-Length:", 15) == 0) {
        /* turn off flag so you know you are no longer in mail
           message header */
        in_header = 0;
        /* clear the old message since this is a new one */
        memset(mesg, NULL, MAXMSGLEN);
        continue;
    }

    /* if the line you are now reading in not part of the mail header
       add it to the message */
    if(in_header == 0) {
        strljust(buff, 512);
        strtrim(buff);
        /* make sure you dont add more than the message length */
        if( (strlen(buff) + strlen(mesg)) < MAXMSGLEN) {
            strcat(mesg, " ");
            strcat(mesg, buff);
        }
    }
}

/* end of read line while */

/* send the last message in the file */
send_mesg(mesg);
}

```


DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name, I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

"ELECTRONIC MAIL SYSTEM WITH RF COMMUNICATIONS TO MOBILE PROCESSORS"

the specification of which (check one)



is attached hereto.



was filed on _____

as Application Serial No. _____

and was amended on _____

(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

None

(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

None

(Application Serial No.)	(Filing Date)	(Status: patented, pending, abandoned)

I hereby appoint as principal attorneys; Donald R. Antonelli, Reg. No. 2,296; and T. Terry, Reg. No. 20,178; Melvin Kraus, Reg. No. 22,466; Stanley A. Wal, Reg. No. 26,432; William I. Solomon, Reg. No. 28,565; Gregory E. Montone, Reg. No. 28,141; Ronald J. Shore, Reg. No. 28,577; Donald E. Stout, Reg. No. 26,422; Alan E. Schiavelli, Reg. No. 32,087 and James N. Dresser, Reg. No. 22,973 to prosecute and transact all business connected with this application and any related United States application and international applications. Please direct all communications to the following address:

Antonelli, Terry, Stout & Kraus
Suite 600
1919 Pennsylvania Avenue, N.W.
Washington, D.C. 20006
Telephone: (202) 828-0300

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Date	<u>May 17, 1991</u>	Inventor	<u>Thomas J. Campana, Jr.</u>	(Full Name)	<u>Thomas Campana</u>	(Signature)
Residence	<u>Same As Post Office Address</u>			Citizenship	<u>U.S.</u>	
Post Office Address	<u>3836 West 86th Street, Chicago, Illinois 60652</u>					
Date	<u>5-17-91</u>	Inventor	<u>Michael P. Ponschke</u>	<u>Michael P. Ponschke</u>		
Residence	<u>Same As Post Office Address</u>			Citizenship	<u>U.S.</u>	
Post Office Address	<u>212 Tara Drive, Lockport, Illinois 60441</u>					
Date	<u>5-17-91</u>	Inventor	<u>Gary F. Thelen</u>	<u>Gary F. Thelen</u>		
Residence	<u>Same As Post Office Address</u>			Citizenship	<u>U.S.</u>	
Post Office Address	<u>16 Fox Lane, Palos Park, Illinois 60464</u>					
Date						
Inventor						
Residence				Citizenship		
Post Office Address						
Date						
Inventor						
Residence				Citizenship		
Post Office Address						
Date						
Inventor						
Residence				Citizenship		
Post Office Address						
Date						
Inventor						
Residence				Citizenship		
Post Office Address						
Date						
Inventor						
Residence				Citizenship		
Post Office Address						
Date						
Inventor						
Residence				Citizenship		
Post Office Address						

Applicant or Patentee: THOMAS J. CAMPANA, JR. et al

Serial or Patent No.: _____ Attorney's Docket No.: 780.29643X00

Filed or Issued: May 20, 1991

For: ELECTRONIC MAIL SYSTEM WITH RF COMMUNICATIONS TO MOBILE PROCESSORS

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(f) and 1.27(b)) - INDEPENDENT INVENTOR

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled "Electronic Mail System With RF Communications to
Mobile Processors" described in

☒ the specification filed herewith.

☐ Application Serial No.: _____, filed: _____

☐ Patent No.: _____, issued: _____

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

☐ no such person, concern, or organization.

☒ persons, concerns, or organizations listed below.*

*NOTE: Separate verified statements are required from each named person, concern, or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27).

FULL NAME: Thomas J. Campana, Jr.

ADDRESS: 3836 West 86th Street, Chicago, Illinois 60652

☒ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

FULL NAME: _____

ADDRESS: _____

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

FULL NAME: _____

ADDRESS: _____

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

(Continued on Page 2)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

THOMAS J. CAMPANA, JR.

NAME OF INVENTOR

Thomas J. Campana, Jr.
Signature of Inventor

May 17 1991
Date

MICHAEL P. PONSCHKE

NAME OF INVENTOR

Michael P. Ponschke
Signature of Inventor

5-17-91
Date

GARY F. THELEN

NAME OF INVENTOR

Gary F. Thelen
Signature of Inventor

5-17-91
Date

SUPPLEMENTAL DECLARATION FOR PATENT APPLICATION

As the below named inventors, we hereby declare that:

Our residence, post office address and citizenship are as stated below next to our names, we believe that we are an original, first and joint inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled:

"ELECTRONIC MAIL SYSTEM WITH RF COMMUNICATIONS TO MOBILE PROCESSORS AND METHOD OF OPERATION THEREOF"

the specification of which was filed on May 20, 1991 as application Serial No. 07/702,939 and as amended in amendments attached hereto including claims 86-176.

We hereby state that we have reviewed and understand the contents of the amendments to the above-identified specification, and newly submitted claims 86-176, as attached.

We acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

We hereby declare that all statements made herein of my our knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Date: June 15, 94

Inventor: Thomas J. Campana, Jr.

Thomas J. Campana, Jr.

Residence: Same As Post Office Address

Post Office Address: 3836 West 86th Street
Chicago, Illinois 60652

Date: 6-15-94

Inventor: Michael P. Ponschke

Michael P. Ponschke

Residence: Same As Post Office Address

Post Office Address: 212 Tara Drive
Lockport, Illinois 60441

Date: 7-1-94

Inventor: Gary F. Thelen

Gary F. Thelen

Residence: Same As Post Office Address

Post Office Address: 16 Fox Lane
Palos Park, Illinois 60464